

SC-51-0100-0001-06

SmartCell Fire Manual Call Point - Swedish

Overview

The SmartCell Call Point is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include a protective transparent cover, bidirectional 868 MHz communication, fire indication LED and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



Details

- Quick and easy to install
- Compact enclosure
- Includes protective transparent cover
- Unique design
- Inbuilt locking mechanism

SC-51-0100-0001-06

SmartCell Fire Manual Call Point - Swedish

Technical specifications

Algemeen

Status indication	LED
Wireless frequency	868 MHz
Compatibility	SmartCell

Elektrisch

Batteries	2 x ER14505M 3.6 V lithium thionyl chloride batteries (Fanso or Titus)
-----------	--

Fysiek

Physical dimensions	92 x 97 x 47 mm (W x H x D)
Net weight	0.2 kg
Colour	Red
Mounting type	Wall mount

Omgeving

Operating temperature	-10 to +55°C
Storage temperature	-10 to +55°C (without batteries)
Relative humidity	95% noncondensing max.
Environment	Indoor

Regelgevend

Compliance	CE
Certification	CPR
Standards	EN54-11 EN54-13 EN54-25



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 3 January 2024 - 11:40