

# 240365

## Conventional EN12094 manual call point, Abort

### General

---

The 240365 is a white, double action manual call point used as electrical abort device in extinguishing systems.

It is connected to the fire detection or extinguishing control panel via a conventional detector line. A red status LED optically indicates the activated condition of the device.

### Construction

---

In comparison with plastic housings, the robust design housing made of die-cast aluminium proves advantages even after years of use thanks to its resistance to environmental impact and minimal colour fading in sunlight. Design details such as the self-closing lock cover protect the inside from dust or water penetration and facilitate easy installation and cabling. The door with the easily replaceable glass pane has an opening angle of more than 180°.

When the call point is activated, the door is mechanically prevented from closing.



### Details

---

- Conventional technology for use in most extinguishing control systems
- LED indication for activation status indication
- EN12094-3 certified
- Operating instructions by means of standardised EN54-11 type symbols
- Attractive design housing made of robust die-cast aluminium
- Designed for surface mount applications
- EN standard type B manual call point, dual action
- 100 Ohm series resistor fitted

# 240365

## Conventional EN12094 manual call point, Abort

### Technical specifications

#### General

Status indication	LED
Compatibility	Conventional detection & alarm systems

#### Electrical

Power supply type	Zone powered
Operating voltage	10 to 30 VDC
Cable specification	<1.5 mm <sup>2</sup>
Terminals	6

#### Detection

Detection principle	Manual activation
Monitoring	Off, On
Installation height	Determined by local regulation

#### Output

Output quantity	1
Output type and rating	Contact (25 VAC @ 2 A or 60 VDC @ 2 A)

#### Physical

Physical dimensions	127 x 127 x 35 mm (W x H x D)
Net weight	± 420 g
Colour	White (RAL 1013)
Mounting type	Surface mount, Wall mount
Cable entries	Top & bottom ( 2 x M20×1.5), Rear wall (2 x 24×10 mm)
Material (body)	Die-cast aluminium
Functional marking	ABORT

#### Environmental

Vandal proof	No
Operating temperature	-25 to +70°C (max. 12 h) (maximum application) -20 to +60°C (continuous operation) (typical application)
Relative humidity	5 to 95% noncondensing
Environment	Indoor
IP rating	IP43 (standard)

#### Regulatory

Compliance	CE, REACH, RoHS 3, WEEE
Certification	EN12094-3



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](https://firesecurityproducts.com) online or contact your sales representative.

Last updated on 2 May 2024 - 14:19