

HWN-2104,HWN-2108 SERIES NVR




Key Features

- Connectable to the third-party network cameras
- Up to 8 network cameras can be connected
- H.264+ compression effectively reduces the storage space and costs by up to 50%
- Full channel recording at up to 4 MP resolution
- HDMI/VGA output at 1080p resolution
- Up to 2-ch synchronous playback at 4 MP resolution or 4-ch at 1080p resolution
- 1 SATA hard disks can be connected with 6TB capacity
- HDD quota and group modes; different capacity can be assigned to different channel
- Supports multiple VCA(Video Content Analytics) events detection
- Smart search for the selected area in the video; and smart playback to improve the playback efficiency
- One-key operation: automatically search, modify and add IP cameras after device is activated
- Hik-Connect and DyDDNS for easy network management
- 100 Mbps Ethernet network interface



Dimensions



| Index | Name | Index | Name |
|-------|-----------------------|-------|---------------|
| 1 | Power Supply | 5 | Audio Out |
| 2 | Audio In | 6 | VGA Interface |
| 3 | HDMI Interface | 7 | USB Interface |
| 4 | LAN Network Interface | 8 | Ground |

| Model | | HWN-2104 | HWN-2108 |
|--------------------|---------------------------------|---|----------|
| Video/Audio input | IP video input | 4-ch | 8-ch |
| | Two-way audio input | 1-ch, RCA (2.0 Vp-p, 1kΩ) | |
| Network | Incoming bandwidth | 40 Mbps | 60 Mbps |
| | Outgoing bandwidth | 40 Mbps | 40 Mbps |
| | Remote connection | 64 | |
| Video/Audio output | Recording resolution | 4 MP/3 MP/1080p/1.3 MP/UXGA/720p/VGA/4CIF/DCIF/2CIF/ CIF/QCIF | |
| | HDMI/VGA output | 1-ch, resolution: 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz | |
| | Audio output | 1-ch, RCA (Linear, 1kΩ) | |
| Decoding | Live view/Playback resolution | 4 MP/3 MP/1080p/1.3 MP/UXGA/720p/VGA/4CIF /DCIF/2CIF/CIF/QCIF | |
| | Capability | 2-ch@4 MP, 4-ch@1080p | |
| Hard disk | SATA | 1 SATA interface for 1 HDD | |
| | Capacity | Up to 6TB for each disk | |
| Network management | Network protocols | TCP/IP, DHCP, Hik-Connect, DDNS, NTP, SADP, SMTP, UPnP™ | |
| External interface | Network interface | 1 RJ-45 10/100 Mbps self-adaptive Ethernet interface | |
| | USB interface | 2 × USB 2.0 | |
| General | Power supply | 12 VDC | |
| | Consumption (without hard disk) | ≤ 10 W | |
| | Working temperature | -10 °C to +55 °C (14 °F to 131 °F) | |
| | Working humidity | 10 % to 90 % | |
| | Dimensions (W × D × H) | 200 × 205 × 48 mm (7.9" × 8.1" × 1.9") | |
| | Weight (without hard disk) | ≤ 1 kg (2.2 lb) | |

Applicable Models

HWN-2104,HWN-2108

Distributed by



HIKVISION[®]
HiWatch Series

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Africa
T +27 (10) 0351172
sale.africa@hikvision.com

Hikvision Europe
T +31-23-55-42-770
info.eu@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Hong Kong
T +852-2151-1761

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Canada
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

Hikvision Korea
T +82-31-731-8841
sales.korea@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision UK
T +01628-902140
support.uk@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com