

TESTIFIRE-XTR2-6M

All-in-one connected smoke/heat detector test kit to 6 m

Powerful insights, automated test reports & records

The Testifire-XTR2 combines testing and reporting to deliver on compliance, giving service companies and building owners the insight and assurance they demand. The Testifire-XTR2 is designed to work with all detector brands and models, and with both addressable and conventional systems.

Test modes

The Testifire-XTR2 supports all-in-one smoke and heat testing including smoke only, heat or hi-heat only, combined and sequential smoke/heat as well as ASD test compatibility.

DT Connect App

Every Testifire-XTR includes a 6-month trial of DT Connect premium. When the 6-month trial period ends, a DT Connect subscription is needed to continue accessing the full range of features. The Testifire-XTR2 can also be used without subscription, albeit with limited features.

DT Connect alongside the Testifire-XTR2, allows advanced features to streamline the testing process, easily manage site assets and optimise reporting capability by automatically generating test reports.

DT Connect allows for:

- Minimising time spent on basic tasks
- Panel time logging to synchronise test and panel event timestamps *
- Test result capturing
- Asset identification *
- Panel reconciliation *
- Job summary
- Shareable reports *

* Premium DT Connect features

Product information

The Testifire-XTR2 kit includes:

- 1 x TESTIFIRE-XTR2-HEAD
- 1 x TESTIFIRE-BP Li-ion Battery
- 1 x TESTIFIRE-GEN Smoke Generator
- 1 x TESTIFIRE-CHAK Charger Kit
- 1 x TES3 Smoke Cartridge
- 1 x ET010 Fibre-glass telescopic pole 4.5 m
- 1 x FG010 Universal removal tool on swing frame
- 1 x CB001 Carrying bag



Details

- Rapid smoke generation saves waiting time
- 50% faster heat and hi-heat activation compared with the legacy TM010
- Sequential & combined test modes including hi-heat testing up to 100°C
- TFT-LCD full colour touch screen user interface
- Automatic LED torch in dark environments
- Automatic test result capture with detector LED recognition support
- Clearing mode to prevent re-alarms
- Robust and repairable
- Bluetooth enables communication to the DT Connect App with 6-month free PREMIUM support
- Optional subscription for premium features in the DT Connect app and Cloud Portal

TESTIFIRE-XTR2-6M

All-in-one connected smoke/heat detector test kit to 6 m

Especificaciones técnicas

Eléctrico

Tipo de fuente de alimentación	Baterías
Voltaje de funcionamiento	10.8 V (35.1 wh / 3250 mAh)
Consumo de corriente	< 0.5 A rms (smoke testing) 4 to 6 A rms (heat testing)

Físico

Dimensiones físicas	406 x 156 x 150 mm
Peso neto	1.25 kg
Peso de envío	2.39 kg
Color	Negro, Gris

Medioambiental

Antivandálico	No
Temperatura de funcionamiento	5 to 45°C (41 to 113°F) - Head unit 5 to 40°C (41 to 104°F) - Charger cradle
Temperatura de almacenamiento	-10 to 50°C (14 to 122°F)
Humedad relativa	0 to 85% non-condensing - operating 0 to 90% non-condensing - storage

Regulador

Cumplimiento	CE, REACH, RoHS 3, WEEE
Certificación	CE

SKU info

Product brand	testifire
---------------	-----------

Test

Carbon Monoxide	No
Heat	Yes
Smoke	Yes

Electrical

Battery type	Lithium Ion
Charging	USB-C connection to charging cradle

Physical

Stimulus type	Cartridge
---------------	-----------

Productos compatibles

Categoría	Referencia	Descripción
Equipos de Prueba	ET011	Elemento de prolongación de 1,2 m. de fibra de vidrio.
Equipos de Prueba	TES3-6PACK	
Equipos de Prueba	TESTIFIRE-ADAP	
Equipos de Prueba	TESTIFIRE-MEM	
Equipos de Prueba	TESTIFIRE-MEML	

Productos compatibles

Categoría	Referencia	Descripción
Equipos de Prueba	TESTIFIRE-SOP	



Como empresa innovadora, Kidde Global Solutions se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.