

TP-Link Omada EAP603-Outdoor 1800 Mbit/s White Power over Ethernet (PoE)



Brand : TP-Link

Product family: Omada

Product code: EAP603-OUTDOOR

Product name : EAP603-Outdoor

- Seamless 1.8Gbps Wi-Fi 6 Speeds: 574 Mbps on 2.4 GHz and 1201 Mbps on 5 GHz.†
- Dual-Band Omnidirectional Coverage: Up to 300 m (984 ft) long-range coverage.*
- PoE+ Powered: Supports both 802.3at PoE and Passive PoE (adapter included)
- Ideal for Outdoor Environments: IP65 weatherproof, 6 kV lightning protection, and a reliable operating range of -40 °C to +70 °C
- Easy and Quick Setup: Wall/pole mounting; Omada SDN for one-click setup
- Advanced Features: Omada Mesh, Seamless Roaming, and Centralized Cloud Management.‡

1x 10M/100M/1000Mbps Gigabit Ethernet Port (RJ45), Wi-Fi 6 2.4 - 5 GHz, 300m, 230 x 207.5 x 69.7 mm

TP-Link Omada EAP603-Outdoor. 2.4 GHz, 5 GHz, Maximum data transfer rate: 1800 Mbit/s. Security algorithms: EAP, EAP-FAST, EAP-GTC, EAP-MD5, EAP-PEAP, EAP-SIM, EAP-TLS, EAP-TTLS, PEAP, PPSK, SNMP, SSH,.... Ethernet LAN data rates: 10,100,1000 Mbit/s. Power over Ethernet (PoE). Product colour: White. Power consumption (max): 4.8 W

Features		Power	
2.4 GHz *	✓	Power over Ethernet (PoE) type supported	Passive PoE
5 GHz *	✓	DC voltage range	42.5 - 57 V
6 GHz *	✗	Input current	0.36 A
Maximum data transfer rate *	1800 Mbit/s	Power consumption (max)	4.8 W
Security		Design	
Maximum data transfer rate (2.4 GHz)	573 Mbit/s	Placement *	Pole, Wall
Maximum data transfer rate (5 GHz)	1201 Mbit/s	Product colour *	White
Ethernet LAN data rates	10,100,1000 Mbit/s	International Protection (IP) code	IP65, IP66
Bluetooth	✓	Antenna	
Maximum outdoor range	300 m	Antenna type *	Internal & external
		Antenna direction type	Omni-directional
		Antennas quantity	4
		Antenna gain level (max)	5 dBi
Certificates		Weight & dimensions	
		Compliance certificates	CE, Federal Communications Commission (FCC), RoHS
Management features		Weight & dimensions	
Web-based management	✓	Width	230 mm
Cloud-managed	✓	Depth	207.5 mm
Backup function	✓	Height	69.7 mm
Ports & interfaces		Packaging content	
Ethernet LAN (RJ-45) ports *	1	PoE adapter included	✓
		Mounting kit	✓
		Quick start guide	✓
Power		Operational conditions	
Power over Ethernet (PoE) *	✓	Operating relative humidity (H-H)	10 - 90%
		Operating temperature (T-T)	-30 - 70 °C
		Storage temperature (T-T)	-40 - 70 °C
		Storage relative humidity (H-H)	5 - 90%



1210002605731

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.