





PORT A 2 3 4 5 6 7 0

. . .

MESH

PORT B 2 3 4 5 0

1

۲



PORT

02 🔍

ИAR

VSS (GND)



HOMES

Grant the safest

protection to your

family even while

you are at home

The best solution

to safeguard your

business property

BUSINESS PREMISES

Target



GARAGES The smartest and

cheapest solution to keep your belongings safe

JEWELLERIES The most effective answer to preserve your jeweler store

SUPERMARKETS We offer resolutions for any need and any space dimension

MONEY EXCHANGE Example of anti robbery application and night protection

WAREHOUSES Protect up to 4000 m³ with only one fogging system









TELCO SHOPS / SHELTERS Telecommunication shelters and shops are primary targets for fogging systems

GAMBLING MACHINES One of the most stroked target - we grant a wide range of solutions - they can also be integrated to the gambling machine

PETROL STATIONS Our fog fluid is certified as not dangerous for people and animals - outdoor and indoor solutions

ATM / BANKS Choose between embedded battery operated machine or standard fogging systems

CAMPERS-CARAVANS-BOATS The unique battery operated answer - Flex

AH14 1111















VUSB

PORT

PO

P-8





ORT

Fog Storm pump technology

PRODUC





CE MARKING

UR FOG S.r.L

a. 2016 May, 23 G.S.D. s.e.l Via Marrisoto, 8 Set21 OSPEDALETTO Tel. 505 504254 - Fax 500.

Nex. H

GSD

G.S.D. Sr PISA - Ital

Location and Date of Is

uufacturer

G.S.D. S.r.I. Cattified in accordance UM EN ESO 9001:20

TEV Rheisland Italia S.r.J. Certificate N. 39 90 1850505

Dattellin

Attestation of Conformity n. 16591-AC-F Rev.

haly FAST 03 2C PRO-P, FAST 01 2C-P FAST 03 1C PRO-P, FAST 02 2C PRO-P G.S.D. S.r.I. eurofins Test Facility

CE MARKING

R Fog S.r.J.

AST 02-03 AST 02

Report n. 13288

TOXICOLOGICAL EVALUATION ON UR FOG CARTRIDGE

Set 15th

The second

SINCERT

A

C.SOC. 4 100001 (x P.NA 90191409 C.F. 037401510 REAM 90000 D-374-5 40911712

UR FOG machines have been developed, thanks to the internal R&D team and laboratories, with innovative solutions for security and fully respecting internationals approvals and regulations.

Fog fluid is certified by EUROFINS, one of the largest multinational company for chemical, cosmetic, medicine certification, as not toxic for humans and animals and fluid content is not in contrast with any islamic country regulation Products have been already sold in Pakistan, Iran, Saudi Arabia, Kuwait and Tunisia and in other 48 worldwide countries.



POR

9P8

6

0

Fogging machines have EMC - FCC - CE approvals and respect EN 50131-8 regulation.



Several innovative and unique security components have been introduced on the market and patented by UR FOG like fuse cables for mechanical temperature security control. Fully internal electronic board and firmware development grant the possibility of modifications on target demands.







Products range

m^e 200

m^e 200



FAST 03 EASY 2

Up to 200 m³ (recommended density) One cylinder 300 ml included Shoots full cylinder in two times Vertical installation Arming, shooting and outputs Adjustable nozzle

FAST 03 2C

Up to 200 m³ (recommended density) Two cylinders 400 ml included Shot programmable in seconds Vertical/horizontal installation Arming, shooting and outputs Adjustable nozzle



FAST 01 2C

Up to 1200 m³ (recommended density) Two cylinders 600 ml included Shot programmable in seconds Vertical/horizontal installation Arming, shooting and outputs Adjustable nozzle

FAST 03 1C PRO PLUS

மீ 200

ന്നീ എന

m³ 1200



Up to 200 m³ (recommended density) One cylinder 600 ml included Shot programmable in seconds Vertical/horizontal installation THREE INPUTS: arming, shooting and PIR sensor validation FOUR OUTPUTS: empty cylinder, fault, tamper, shot confirmation Adjustable nozzle

FAST 02 2C PRO PLUS Up to 400 m³ (recommended density)

Two cylinders 600 ml included Shot programmable in seconds Vertical/horizontal installation THREE INPUTS: arming, shooting and PIR sensor validation FOUR OUTPUTS: empty cylinder, fault, tamper, shot confirmation Adjustable nozzle



FAST 03 2C PRO PLUS

Up to 200 m³ (recommended density) Two cylinders 600 ml included Shot programmable in seconds Vertical/horizontal installation THREE INPUTS: arming, shooting and PIR sensor validation FOUR OUTPUTS: empty cylinder, fault, tamper, shot confirmation Adjustable nozzle

FAST 01 2C PRO PLUS

กาย กลาม

2

 $m^{2}200$

Up to 1200 m³ (recommended density) Two cylinders 600 ml included Shot programmable in seconds Vertical/horizontal installation THREE INPUTS: arming, shooting and PIR sensor validation FOUR OUTPUTS: empty cylinder, fault, tamper, shot confirmation Adjustable nozzle

FAST 02 2C Up to 400 m³ (recommended density) Two cylinders 500 ml each included Shot programmable in seconds Vertical/horizontal installation

FAST 03 1C

Adjustable nozzle

Up to 200 m³ (recommended density)

One cylinder 400 ml included

Vertical/horizontal installation

Arming, shooting and outputs

Arming, shooting and outputs

Adjustable nozzle

Shot programmable in seconds



ന്നീ മന്ന

PORI

VUSB (5V)







Products range



FAST 03 EASY PUMP

Up to 200 m³ (recommended density) One bag 500 ml included Shot programmable in seconds Vertical/horizontal Arming, shooting and outputs

m^e ADD

ாீ கற



FAST 250 PUMP PRO PLUS

Up to 250 m³ (recommended density) One bag 1000 ml included Shot programmable in seconds Vertical/horizontal installation THREE INPUTS: arming, shooting and PIR sensor validation FOUR OUTPUTS: empty cylinder, fault, tamper, shot confirmation Adjustable nozzle



FAST 500 PUMP PRO PLUS

Up to 500 m³ (recommended density) One bag 1000 ml included Shot programmable in seconds Vertical installation THREE INPUTS: arming, shooting and PIR sensor validation FOUR OUTPUTS: empty cylinder, fault, tamper, shot confirmation Adjustable nozzle



FAST 1500 PUMP PRO PLUS m⁸ fl気の

Up to 1500 m³ (recommended density) One bag 1000 ml included Shot programmable in seconds Vertical/horizontal installation THREE INPUTS: arming, shooting and PIR sensor validation FOUR OUTPUTS: empty cylinder, fault, tamper, shot confirmation Adjustable nozzle



VUSB (

FAST 4000 PUMP PRO PLUS

ш⁹ 4000 Up to 4000 m³ (recommended density) One bag 4000 ml included Shot programmable in seconds Vertical installation THREE INPUTS: arming, shooting and PIR sensor validation FOUR OUTPUTS: empty cylinder, fault, tamper, shot confirmation

FLEX

m⁹ 750

ாீ தற

Ρ 2

ന്നീ മണ

Up to 750 m³ One bag 500 ml included Shot programmable in seconds Battery operated only Battery duration over 3 months without recharging it

ELLIPSE 250 PUMP PRO PLUS $100^{32} 250$

- Up to 250 m³ (recommended density)
- One bag 1000 ml included

Adjustable nozzle

- Shot programmable in seconds
- Vertical/horizontal installation
 - THREE INPUTS: arming, shooting and PIR sensor validation FOUR OUTPUTS: empty cylinder, fault, tamper, shot confirmation Adjustable nozzle



ELLIPSE 500 PUMP PRO PLUS

- Up to 500 m³ (recommended density) One bag 1000 ml included
- Shot programmable in seconds Vertical/horizontal installation

THREE INPUTS: arming, shooting and PIR sensor validation FOUR OUTPUTS: empty cylinder, fault, tamper, shot confirmatio Adjustable nozzle





हू FAST LINE

ROA

 \leq

(5V)

fog

| | ASILINE | FAST 03 EASY 2 | FAST 03 1C | FAST 03 2C | FAST 02 2C | FAST 01 2C |
|---|--------------------------------------|----------------------|----------------------|----------------------|----------------------|----------------------|
| _ | MAX FOG EMISSION IN A SINGLE SHOT | 200 m ³ | 200 m ³ | 200 m ³ | 400 m ³ | 1200 m ³ |
| | MAX SECONDS IN A SINGLE SHOT | 15 sec | 15 sec | 15 sec | 25 sec | 70 sec |
| | TOTAL EMISSION WITH FULL FOG TANKS | 400 m ³ | 600 m ³ | 1200 m ³ | 1500 m ³ | 1800 m ³ |
| 4 | CYLINDERS OR PUMP | 1 CYLINDER | 1 CYLINDER | 2 CYLINDERS | 2 CYLINDERS | 2 CYLINDERS |
| ٢ | FOG TANK CAPACITY | 300 ml | 400 ml | 400 ml | 500 ml | 600 ml |
| | WORKING TIME WITHOUT MAINS POWER | ABOUT 2 H | ABOUT 2 H | ABOUT 2 H | ABOUT 2 H | OVER 2,5 H |
| L | HEATING TIME | ABOUT 70 min. | ABOUT 70 min. | ABOUT 70 min. | ABOUT 90 min. | ABOUT 2 H |
| | VERTICAL/CORNER MOUNTING | BOTH | BOTH | BOTH | BOTH | VERTICAL |
| | HORIZONTAL MOUNTING | ND | YES | YES | YES | YES |
| 2 | SERIAL PORT FOR BUS | YES | YES | YES | YES | YES |
| 2 | AVERAGE POWER CONSUMPTION | 37 W | 37 W | 37 W | 42 W | 60 W |
| 4 | BACK UP BATTERY | 6 ALCALINE BATTERIES |
| 2 | ELECTRONIC BOARD | FAST | FAST | FAST | FAST | FAST |
| | CABINET TYPE | FAST | FAST | FAST | FAST | FAST |
| | FOG FLUID CERTIFIED AS NOT DANGEROUS | YES | YES | YES | YES | YES |
| | EUROPEAN STANDARD CERTIFICATIONS | YES | YES | YES | YES | YES |
| | | | | | | |

| PUMP LINE | | | | | | |
|-----------|--------------------------------------|---------------------------|---------------------------|---------------------|---------------------|---------------------|
| | | EASY PUMP | PUMP 250 | PUMP 500 | PUMP 1500 | PUMP 4000 |
| ĩ | MAX FOG EMISSION IN A SINGLE SHOT | 200 m ³ | 250 m ³ | 500 m ³ | 1500 m ³ | 4000 m ³ |
| 5 | MAX SECONDS IN A SINGLE SHOT | 35 sec | 30 sec | 30 sec | 70 sec | 3 min |
| - | TOTAL EMISSION WITH FULL FOG TANKS | 750 m ³ | 750 m ³ | 1500 m ³ | 1500 m ³ | 4000 m ³ |
| | CYLINDERS OR PUMP | STANDARD PUMP | FOG STORM PUMP | FOG STORM PUMP | FOG STORM PUMP | FOG STORM PUMP |
| | FOG TANK CAPACITY | 500 ml PLASTIC BAG | 1 L PLASTIC BAG | 1 L PLASTIC BAG | 1 L PLASTIC BAG | 4 L PLASTIC BAG |
| | WORKING TIME WITHOUT MAINS POWER | ABOUT 2 H | ABOUT 2 H | ABOUT 2 H | ABOUT 2,5 H | 5 H |
| | HEATING TIME | ABOUT 70 min. | ABOUT 70 min. | ABOUT 70 min. | ABOUT 2 H | 8 H |
| | VERTICAL/CORNER MOUNTING | VERTICAL | VERTICAL | VERTICAL | VERTICAL | VERTICAL |
| vı | HORIZONTAL MOUNTING | YES | YES | YES | YES | ND |
| | SERIAL PORT FOR BUS | YES | YES | YES | YES | YES |
| | AVERAGE POWER CONSUMPTION | 37 W | 37 W | 42 W | 60 W | 80 W |
| | BACK UP BATTERY | 6 ALCALINE BATTERIES | 2 Ah | 2 Ah | 2 Ah | 2 Ah |
| | ELECTRONIC BOARD | FAST | PLUS | PLUS | PLUS | PLUS |
| | CABINET TYPE | FAST | PRO | PRD | PRO | PRO |
| | FOG FLUID CERTIFIED AS NOT DANGEROUS | YES | YES | YES | YES | YES |
| | EUROPEAN STANDARD CERTIFICATIONS | YES | YES | YES | YES | YES |
| | | | | | | |

P 1 2



PRO PLUS LINE

 \mathbf{O}

POR

JP8 O

edf e

(5V)

| PRU PLUS LINE | | FAST 03 1C PRO PLUS | FAST 03 2C PRO PLUS | FAST 02 2C PRO PLUS | FAST 01 2C PRO PLUS |
|---------------|--------------------------------------|---------------------|---------------------|---------------------|---------------------|
| ⊢ ا | MAX FOG EMISSION IN A SINGLE SHOT | 200 m ³ | 200 m ³ | 400 m ³ | 1200 m ³ |
| | MAX SECONDS IN A SINGLE SHOT | 15 sec | 15 sec | 25 sec | 70 sec |
| | TOTAL EMISSION WITH FULL FOG TANKS | 900 m ³ | 1800 m ³ | 1800 m ³ | 1800 m ³ |
| <u> </u> | CYLINDERS OR PUMP | 1 CYLINDER | 2 CYLINDERS | 2 CYLINDERS | 2 CYLINDERS |
| ے ا | FOG TANK CAPACITY | 600 ml | 600 ml | 600 ml | 600 ml |
| <u> </u> | WORKING TIME WITHOUT MAINS POWER | ABDUT 2 H | ABOUT 2 H | ABOUT 2 H | ABOUT 2,5 H |
| 9 | HEATING TIME | ABOUT 70 min. | ABOUT 70 min. | ABOUT 90 min. | ABOUT 2 H |
| 3 | VERTICAL/CORNER MOUNTING | VERTICAL | VERTICAL | VERTICAL | VERTICAL |
| | HORIZONTAL MOUNTING | YES | YES | YES | YES |
| 1 | SERIAL PORT FOR BUS | YES | YES | YES | YES |
| PO | AVERAGE POWER CONSUMPTION | 37 W | 37 W | 42 W | 60 W |
| R | BACK UP BATTERY | 2 Ah | 2 Ah | 2 Ah | 2 Ah |
| 0 | ELECTRONIC BOARD | PRO PLUS | PRO PLUS | PRO PLUS | PRO PLUS |
| | CABINET TYPE | PRD | PRO | PRD | PRO |
| | FOG FLUID CERTIFIED AS NOT DANGEROUS | YES | YES | YES | YES |
| | EUROPEAN STANDARD CERTIFICATIONS | YES | YES | YES | YES |
| | | | | | |

ELLIPSE LINE

| | ELLIPSE 250 | ELLIPSE 500 |
|--------------------------------------|---------------------|---------------------|
| MAX FOG EMISSION IN A SINGLE SHOT | 250 m ³ | 500 m ³ |
| MAX SECONDS IN A SINGLE SHOT | 30 sec | 30 sec |
| TOTAL EMISSION WITH FULL FOG TANKS | 1500 m ³ | 1500 m ³ |
| CYLINDERS OR PUMP | FOG STORM PUMP | FOG STORM PUMP |
| FDG TANK CAPACITY | 1 L PLASTIC BAG | 1 L PLASTIC BAG |
| WORKING TIME WITHOUT MAINS POWER | ABOUT 2 H | ABOUT 2 H |
| HEATING TIME | ABOUT 70 min. | ABOUT 70 min. |
| VERTICAL/CORNER MOUNTING | VERTICAL | VERTICAL |
| HORIZONTAL MOUNTING | YES | YES |
| SERIAL PORT FOR BUS | YES | YES |
| AVERAGE POWER CONSUMPTION | 37 W | 37 W |
| BACK UP BATTERY | 2 Ah | 2 Ah |
| ELECTRONIC BOARD | PLUS | PLUS |
| CABINET TYPE | ELLIPSE | ELLIPSE |
| FOG FLUID CERTIFIED AS NOT DANGEROUS | YES | YES |
| EUROPEAN STANDARD CERTIFICATIONS | YES | YES |
| | | |

FLEX 500 m³ 8 min. 750 m³ PUMP 500 ml PLASTIC BAG OVER 3 MONTHS 2 sec. VERTICAL ND YES 0,25 W 70 Ah FLEX FLEX YES YES





Electronic boards



ŏ

FAST board



Standard board for FAST line and Easy models, battery pack with 6 alcaline batteries.



Plus board with additional PIR input and shooting confirmation output for PRO PLUS machines with 12 V power supply and 2 Ah battery.

Technology

FLEX board



FLEX board for fully battery operated machine; it can work over 3 months without mains power with 70 Ah battery.

VUSB

Fog Storm pump technology



NEW FOG STORM PUMP THAT EQUIPS PUMP PRO PLUS FOGGING SYSTEMS; IT IS AN OUSTANDING NEW MECHANICAL PUMP TECHNOLOGY, THE SPEEDEST AND MOST RELIABLE



2

EASY TO CHANGE, DISPOSABLE FOG CYLIDERS, PATENTED DOUBLE CYLINDER TECHNOLOGY





FAST LINE

PORT

0

Fog machines able to protect small and large areas as they cover volume spaces from 200 m³ to 1200 m³ based on the model. Cylinder shot technology, professional and really price aggressive line.





FAST ELECTRONIC BOARD

| RECHARGE | VERTICAL Horizontal | LIQUID QUANTITY (ml) | FOG MACHINE Model |
|----------|------------------------|-------------------------|--------------------------|
| Î. | VERTICAL | 300 | FAST 03 EASY 2 |
| Î. | VERTICAL HORIZONTAL | 400 | FAST 03 1C FAST 03 2C |
| | VERTICAL HORIZONTAL | 500 | FAST 02 2C |
| | VERTICAL HORIZONTAL | 600 | FAST 01 2C |



BATTERY PACK



ADJUSTABLE NOZZLE



ORT

EASY TO CHANGE CYLINDER





0

FAST 03 EASY 2

ODEOLEICATIO

UR FOG

It is the ideal fogging system to protect small or medium areas like shops, homes, garages. The machine shoots the cylinder content in two times, then you just replace it with a new one in a very easy way. Each shot covers 200 m³ in 15 seconds. The price of Fast 03 Easy 2 is the most aggressive in

M³ 200

the market but its performances are comparable to a top professional machine as speed of fog ejection.

Powerful and fast fogging system, can cover up to 200 m³ each shot.

The densest fog among all the fogging systems thanks to 80% of glycol in its fog fluid and the proprietary shooting technology.

Removable and disposable fog cylinder, very easy to change and with a very competitive price.

Thanks to the massive insulation UR FOG fogging systems have a very low power consumption and can shoot for a long time in absence of mains power; temperature is constantly stable.

A unique serial bus to plug on the electronic board an add on card that allows to easily interface the machine with alarms and to control the fogging system even from remote. A standard protocol is available for all machines.

UR FOG fogging systems are innovative in their technology and performances, in order to guarantee the most effective protection against thefts and they have different patents.

UR FOG fogging systems are certified after European regulation. Fog fluid is assessed as not dangerous for people and animals and does not leave residuals. PORT





m³ 200

FAST 03 1C

DOT KU

0

It is the ideal fogging system to protect small and medium areas like shops, homes, bank ATM machines. It is the entry level of the professional line, shoots up to 200 m³ of dense fog in 15 seconds. It is equipped with a single cylinder and shooting time can be set in seconds. It is very fast and competitive.

| | GENERAL SPECIFICATIONS | |
|--------|--|--------------------------------|
| | WEIGHT OF THE FOG MACHINE | ABOUT 9 KG |
| ł | WEIGHT WITH PACKAGING | ABOUT 11 KG |
| 1 | UNITS ON ONE PALLET 100X120 | 30 |
| | DIMENSION OF THE MACHINE | 26,5X23,0XH34,5 |
| | DIMENSION OF THE PACKAGING | 32,0X25,0XH43,0 |
| | COLORS | WHITE |
| l | WORKING TIME WITHOUT MAINS POWER | ABOUT 2 HOURS |
| 8 | HEAT UP TIME FROM COLD | ABOUT 70 MINUTES |
| 10 | VERTICAL OR CORNER MOUNTING | YES |
| | HORIZONTAL MOUNTING | YES |
| | SERIAL USB PORT FOR MONITORING | YES |
| | NOZZLE TAMPER | YES |
| | SERIAL BUS FOR STANDARD PROTOCOL | YES |
| | ALARM KIT | OPTIONAL |
| | FOG GENERATOR | |
| | NEW HEATING SYSTEM PLUS | YES |
| ę | MAX FOG SINGLE SHOT (1,5 M VISIBILITY) | Up to 300 m ³ |
| ñ | MAX FOG SINGLE SHOT (RECOMMENDED DENS | SITY) Up to 200 m ³ |
| \geq | MAX SECONDS OF FOG EMISSSION | 15 sec |
| | MAX FOG EMITTED WITH FULL FOG TANK | 600 m ³ |
| 2 | NUMBER OF CYLINDERS | 1 |
| | FOG TANK CAPACITY | 1 x 400 ml |
| | SHOOTING SPECIFICATION | PROGRAMMABLE IN SECONDS |
| | CYLINDER MODEL | VERTICAL / HORIZONTAL |
| | CYLINDER INCLUDED | 1 |
| | ELECTRICAL SPECIFICATIONS | |
| _ | POWER SUPPLY | 220 V or 110 V |
| đ | AVERAGE POWER CONSUMPTION | 37 W |
| | BACK UP BATTERY | YES |
| C | OPTIONAL DEMO/ANTIROBBERY KIT | YES |
| 2 | WIRED INPUTS ARMING AND SHOOTING | YES |
| h | WIRED OUTPUTS | YES |
| | STANDARD COMMUNICATION PROTOCOL | YES |
| - | STANDARDS | |
| כ | COMPLIES WITH EUROPEAN CE | YES |
| F | FOG FLUID IS CERTIFIED | YES |
| | MEETS EUROPEAN STANDARD | YES |

Powerful and fast fogging system, can cover up to 200 m³ in 15 seconds.

The densest fog among all the fogging systems thanks to 80% of glycol in its fog fluid and the proprietary shooting technology.

Removable and disposable fog cylinder, very easy to change and with a very competitive price.

Thanks to the massive insulation UR FOG fogging systems have a very low power consumption and can shoot for a long time in absence of mains power; temperature is constantly stable.

Another exclusive, patented and very useful plus that allows to detect automatically if the nozzle is tampered and sends an advise signal.

A unique serial bus to plug on the electronic board an add on card that allows to easily interface the machine with alarms and to control the fogging system even from remote. A standard protocol is available for all machines.

UR FOG fogging systems are innovative in their technology and performances, in order to guarantee the most effective protection against thefts and they have different patents.

UR FOG fogging systems are certified after European regulation. Fog fluid is assessed as not dangerous for people and animals and does not leave residuals.



œ



<u>m³ 200</u>

FAST 03 2C

12 דסק

0

R

œ

PORT

VUSB (5V)

It is the ideal fogging system to protect small and medium areas like shops, homes, bank ATM machines and generally all professional applications where is needed a top security technology. It is equipped with two cylinders for a very convenient, reliable and redundant shooting, shoots up to 200 m³ of dense fog in 15 seconds. It is very fast and competitive.

| GENERAL SPECIFICATIONS | |
|--|----------------------------|
| WEIGHT OF THE FOG MACHINE | ABOUT 11 KG |
| WEIGHT WITH PACKAGING | ABOUT 13 KG |
| UNITS ON ONE PALLET 100X120 | 30 |
| DIMENSION OF THE MACHINE | 26,5X23,0XH34,5 |
| DIMENSION OF THE PACKAGING | 32,0X25,0XH43,0 |
| COLORS | WHITE |
| WORKING TIME WITHOUT MAINS POWER | ABOUT 2 HOURS |
| HEAT UP TIME FROM COLD | ABOUT 70 MINUTES |
| VERTICAL OR CORNER MOUNTING | YES |
| HORIZONTAL MOUNTING | YES |
| SERIAL USB PORT FOR MONITORING | YES |
| NOZZLE TAMPER | YES |
| SERIAL BUS FOR STANDARD PROTOCOL | YES |
| ALARM KIT | OPTIONAL |
| FOG GENERATOR | |
| NEW HEATING SYSTEM PLUS | YES |
| MAX FOG SINGLE SHOT (1,5 M VISIBILITY) | UP TO 300 m ³ |
| MAX FOG SINGLE SHOT (RECOMMENDED DENSITY |) UP TO 200 m ³ |
| MAX SECONDS OF FOG EMISSSION | 15 sec |
| MAX FOG EMITTED WITH FULL FOG TANK | 1200 m ³ |
| NUMBER OF CYLINDERS | 2 |
| FOG TANK CAPACITY | 2 x 400 ml |
| SHOOTING SPECIFICATION | PROGRAMMABLE IN SECONDS |
| CYLINDER MODEL | VERTICAL / HORIZONTAL |
| CYLINDER INCLUDED | 2 |
| DOUBLE FOG TANK ADVANTAGE | YES |
| ELECTRICAL SPECIFICATIONS | |
| POWER SUPPLY | 220 V or 110 V |
| AVERAGE POWER CONSUMPTION | 37 W |
| BACK UP BATTERY | YES |
| OPTIONAL DEMO/ANTIROBBERY KIT | YES |
| WIRED INPUTS ARMING AND SHOOTING | YES |
| WIRED OUTPUTS | YES |
| STANDARD COMMUNICATION PROTOCOL | YES |
| STANDARDS | |
| COMPLIES WITH EUROPEAN CE | YES |
| FOG FLUID IS CERTIFIED | YES |
| MEETS EUROPEAN STANDARD | YES |
| | |

MADE IN ITALY PRODUCT

The densest fog among all the fogging systems thanks to 80% of glycol in its fog fluid and the proprietary shooting technology. Patented double fog cylinder is the best solution to shoot fog, tanks are easy to change and disposable. When the first cylinder is empty the machine switches automatically to the second one even during the same shot. Thanks to the massive insulation UR FOG fogging systems have a very low power consumption and can shoot for a long time in absence of mains power; temperature is constantly stable. Another exclusive, patented and very useful plus that allows to detect automatically if the nozzle is tampered and sends an advise signal. A unique serial bus to plug on the electronic board an add on card that allows to easily interface the machine with alarms and to control the fogging system even from remote. A standard protocol is available for all machines. UR FOG fogging systems are innovative in their technology and performances, in order to TENTEI guarantee the most effective protection against thefts and they have different patents.

> P 2

UR FOG fogging systems are certified after European regulation. Fog fluid is assessed as not dangerous for people and animals and does not leave residuals.

Powerful and fast fogging system, can cover up

to 200 m³ in 15 seconds.



PORT

VUSB (5V)

VU

C6



M³ ADI

FAST 02 2C

UR FOG

0

It is the ideal fogging system to protect medium areas like large shops, homes, and generally all professional applications where a top security technology is needed. It is equipped with two cylinders for a very convenient, reliable and redundant shooting, shoots up to 400 m³ of dense fog in 25 seconds. It is very fast and competitive.

| GENERAL SPECIFICATIONS | |
|---|-----------------------------|
| WEIGHT OF THE FOG MACHINE | ABOUT 15 KG |
| WEIGHT WITH PACKAGING | ABOUT 18 KG |
| UNITS ON ONE PALLET 100X120 | 24 |
| DIMENSION OF THE MACHINE | 30,5X23,0XH39,0 |
| DIMENSION OF THE PACKAGING | 37,0X25,0XH47,0 |
| COLORS | WHITE |
| WORKING TIME WITHOUT MAINS POWER | ABOUT 2 HOURS |
| HEAT UP TIME FROM COLD | ABOUT 90 MINUTES |
| VERTICAL OR CORNER MOUNTING | YES |
| HORIZONTAL MOUNTING | YES |
| SERIAL USB PORT FOR MONITORING | YES |
| NOZZLE TAMPER | YES |
| SERIAL BUS FOR STANDARD PROTOCOL | YES |
| ALARM KIT | OPTIONAL |
| FOG GENERATOR | |
| NEW HEATING SYSTEM PLUS | YES |
| MAX FOG SINGLE SHOT (1,5 M VISIBILITY) | UP TO 600 m ³ |
| MAX FOG SINGLE SHOT (RECOMMENDED DENSITY | γ) UP TO 400 m ³ |
| MAX SECONDS OF FOG EMISSSION | 25 sec |
| MAX FOG EMITTED WITH FULL FOG TANK | 1500 m ³ |
| NUMBER OF CYLINDERS | 2 |
| FOG TANK CAPACITY | 2 x 500 ml |
| SHOOTING SPECIFICATION | PROGRAMMABLE IN SECONDS |
| CYLINDER MODEL | VERTICAL / HORIZONTAL |
| CYLINDER INCLUDED | 2 |
| DOUBLE FOG TANK ADVANTAGE | YES |
| ELECTRICAL SPECIFICATIONS | |
| POWER SUPPLY | 220 V or 110 V |
| AVERAGE POWER CONSUMPTION | 42 W |
| BACK UP BATTERY | YES |
| OPTIONAL DEMO/ANTIROBBERY KIT | YES |
| WIRED INPUTS ARMING AND SHOOTING | YES |
| WIRED OUTPUTS | YES |
| STANDARD COMMUNICATION PROTOCOL | YES |
| STANDARDS | YES |
| | YES |
| FOG FLUID IS CERTIFIED MEETS EUROPEAN STANDARD | YES |
| | TES |
| | |



Powerful and fast fogging system, can cover up to 400 m³ in 25 seconds. The densest fog among all the fogging systems thanks to 80% of glycol in its fog fluid and the proprietary shooting technology. Patented double fog cylinder is the best TENTEI

solution to shoot fog, tanks are easy to change and disposable. When the first cylinder is empty the machine switches automatically to the second one even during the same shot.

Thanks to the massive insulation UR FOG fogging systems have a very low power consumption and can shoot for a long time in absence of mains power; temperature is constantly stable.

Another exclusive, patented and very useful plus that allows to detect automatically if the nozzle is tampered and sends an advise signal.

A unique serial bus to plug on the electronic board an add on card that allows to easily interface the machine with alarms and to control the fogging system even from remote. A standard protocol is available for all machines.

UR FOG fogging systems are innovative in their technology and performances, in order to guarantee the most effective protection against thefts and they have different patents.

UR FOG fogging systems are certified after European regulation. Fog fluid is assessed as not dangerous for people and animals and does not leave residuals.



M³ 1200

ORT

FAST 01 2C

טרא דטה

(2)

20

1

It is the most powerful machine in the market, ideal to protect large areas like big shops, warehouses, superstores or even to protect targets in open space. Shoots 1200 m³ of dense fog in 70 seconds. It is equipped with two removable fog cylinders.

| GENERAL SPECIFICATIONS | |
|---|---------------------------|
| WEIGHT OF THE FOG MACHINE | ABOUT 22 KG |
| WEIGHT WITH PACKAGING | ABOUT 25 KG |
| UNITS ON ONE PALLET 100X120 | 12 |
| DIMENSION OF THE MACHINE | 30,0X35,0XH43,0 |
| DIMENSION OF THE PACKAGING | 51,0X39,0XH52,5 |
| COLORS | WHITE |
| WORKING TIME WITHOUT MAINS POWER | OVER 2,5 HOURS |
| HEAT UP TIME FROM COLD | ABOUT 2 HOURS |
| VERTICAL MOUNTING | YES |
| HORIZONTAL MOUNTING | YES |
| SERIAL/USB PORT FOR MONITORING | YES |
| NOZZLE TAMPER | YES |
| SERIAL BUS FOR STANDARD PROTOCOL | YES |
| | OPTIONAL |
| FOG GENERATOR NEW HEATING SYSTEM PLUS | YES |
| MAX FOG SINGLE SHOT (1,5 M VISIBILITY) | UP TO 1800 m ³ |
| MAX FOG SINGLE SHOT (1,5 M VISIBLETT) MAX FOG SINGLE SHOT (RECOMMENDED DENSITY | |
| MAX FOR SINGLE SHOT (RECOMMENDED DENSITY MAX SECONDS OF FOG EMISSSION | 70 sec |
| MAX SECONDS OF FOR EMISSION MAX FOG EMITTED WITH FULL FOG TANK | 1800 m ³ |
| NUMBER OF CYLINDERS | 2 |
| FOG TANK CAPACITY | 2 x 600 ml |
| SHOOTING SPECIFICATION | PROGRAMMABLE IN SECONDS |
| CYLINDER MODEL | VERTICAL / HORIZONTAL |
| CYLINDER INCLUDED | 2 |
| DOUBLE FOG TANK ADVANTAGE | YES |
| ELECTRICAL SPECIFICATIONS | |
| POWER SUPPLY | 220 V or 110 V |
| AVERAGE POWER CONSUMPTION | 60 W |
| BACK UP BATTERY | YES |
| OPTIONAL DEMO/ANTIROBBERY KIT | YES |
| WIRED INPUTS ARMING AND SHOOTING | YES |
| WIRED OUTPUTS | YES |
| STANDARD COMMUNICATION PROTOCOL | YES |
| STANDARDS | |
| COMPLIES WITH EUROPEAN CE | YES |
| FOG FLUID IS CERTIFIED | YES |
| MEETS EUROPEAN STANDARD | YES |

EUROPEAN STANDARD



The fastest and most powerful machines shooting up to 1200 m^3 in 70 seconds.

The densest fog among all the fogging systems thanks to 80% of glycol in its fog fluid and the proprietary shooting technology.

Patented double fog cylinder is the best solution to shoot fog, tanks are easy to change and disposable. When the first cylinder is empty the machine switches automatically to the second one even during the same shot.

Thanks to the massive insulation UR FOG fogging systems have a very low power consumption and can shoot for a long time in absence of mains power; temperature is constantly stable.

Another exclusive, patented and very useful plus that allows to detect automatically if the nozzle is tampered and sends an advise signal.

A unique serial bus to plug on the electronic board an add on card that allows to easily interface the machine with alarms and to control the fogging system even from remote. A standard protocol is available for all machines.

UR FOG fogging systems are innovative in their technology and performances, in order to guarantee the most effective protection against thefts and they have different patents.

UR FOG fogging systems are certified after European regulation. Fog fluid is assessed as not dangerous for people and animals and does not leave residuals.



VU

C

PORT



FAST PRO PLUS LINE

New generation machines with cylinder technology. Powerful and fast, they are able to protect small and large areas as they cover volume spaces from 200 m³ to 1200 m³ based on the model. PRO cabinet with 600 ml cylinders, resistant to vibrations. It includes power supply to add a 2 Ah battery.





PLUS ELECTRONIC BOARD

| RECHARGE | VERTICAL Horizontal | LIQUID QUANTITY (mi) | FOG MACHINE Model |
|----------|------------------------|-------------------------|--|
| | VERTICAL | 600 | Fast 03 1C PRO PLUS Fast 03 2C PRO PLUS Fast 02 2C PRO PLUS Fast 01 2C PRO PLUS |
| ļ | HORIZONTAL | 600 | Fast 03 1C PRO PLUS Fast 03 2C PRO PLUS Fast 02 2C PRO PLUS Fast 01 2C PRO PLUS |



ADJUSTABLE NOZZLE THAT EQUIPS FAST PRO PLUS FOGGING SYSTEM

POWER SUPPLY AND 2Ah BATTERY INSTALLED IN PRO PLUS FOGGING

(BATTERY NOT INCLUDED)

SYSTEMS





ORT

DOUBLE CYLINDER PATENTED TECHNOLOGY

PORT



ORIE







FAST 03 1C PRO PLUS

UR FOG

It is the ideal fogging system to protect medium areas like large shops, homes, and generally all professional applications where is needed a top security technology. It is equipped with one cylinder for a very convenient, reliable and redundant shooting, shoots up to 200 m³ of dense fog in 15 seconds. It is very fast and competitive. It is prearranged to an easy wall installation and it has a lower compartment to eventually equip boards or accessories.

| | GENERAL SPECIFICATIONS | |
|---|--|--------------------------|
| | WEIGHT OF THE FOG MACHINE | ABOUT 11 KG |
| | WEIGHT WITH PACKAGING | ABOUT 13 KG |
| | UNITS ON ONE PALLET 100X120 | 24 |
| | DIMENSION OF THE MACHINE | 27,5X23,0Xh44,0 |
| 1 | DIMENSION OF THE PACKAGING | 37,0X25,0XH47,0 |
| | COLORS | WHITE |
| | WORKING TIME WITHOUT MAINS POWER | ABOUT 2 HOURS |
| | HEAT UP TIME FROM COLD | ABOUT 70 MINUTES |
| | VERTICAL OR CORNER MOUNTING | YES |
| | HORIZONTAL MOUNTING | YES |
| | SERIAL USB PORT FOR MONITORING | YES |
| | NOZZLE TAMPER | YES |
| | SERIAL BUS FOR STANDARD PROTOCOL | YES |
| | ALARM KIT | OPTIONAL |
| | FOG GENERATOR | |
| | NEW HEATING SYSTEM PLUS | YES |
| ÷ | MAX FOG SINGLE SHOT (1,5 M VISIBILITY) | UP TO 300 m ³ |
| 2 | MAX FOG SINGLE SHOT (RECOMMENDED DENSITY | , |
| | MAX SECONDS OF FOG EMISSSION | 15 sec |
| | MAX FOG EMITTED WITH FULL FOG TANK | 900 m ³ |
| | NUMBER OF CYLINDERS | 1 |
| | FOG TANK CAPACITY | 1 x 600 ml |
| 1 | SHOOTING SPECIFICATION | PROGRAMMABLE IN SECONDS |
| | CYLINDER MODEL | VERTICAL / HORIZONTAL |
| ł | | 1 |
| , | ELECTRICAL SPECIFICATIONS POWER SUPPLY | 220 V or 110 V |
| L | AVERAGE POWER CONSUMPTION | 37 W |
| 2 | BACK UP BATTERY | YES |
| r | OPTIONAL DEMO/ANTIROBBERY KIT | YES |
| | INPUTS WIRED ARMING AND SHOOTING | YES |
| | OUTPUTS WIRED ANMING AND SHOOTING | YES |
| | STANDARD COMMUNICATION PROTOCOL | YES |
| | STANDARD COMMONICATION PROTOCOL | |
| | COMPLIES WITH EUROPEAN CE | YES |
| | FOG FLUID IS CERTIFIED | YES |
| | MEETS EUROPEAN STANDARD | YES |
| 1 | | |



Powerful and fast fogging system, can cover up to 200 m³ each shot.

The densest fog among all the fogging systems thanks to 80% of glycol in its fog fluid and the proprietary shooting technology.

Removable and disposable fog cylinder, very easy to change and with a very competitive price.

Thanks to the massive insulation UR FOG fogging systems have a very low power consumption and can shoot for a long time in absence of mains power; temperature is constantly stable.

Another exclusive, patented and very useful plus that allows to detect automatically if the nozzle is tampered and sends an advise signal.

A unique serial bus to plug on the electronic board an add on card that allows to easily interface the machine with alarms and to control the fogging system even from remote. A standard protocol is available for all machines.

UR FOG fogging systems are innovative in their technology and performances, in order to guarantee the most effective protection against thefts and they have different patents.

UR FOG fogging systems are certified after European regulation. Fog fluid is assessed as not dangerous for people and animals and does not leave residuals.



P 2



PORT

VUSB (5V)

FAST 03 2C PRO PLUS

UR FOG

It is the ideal fogging system to protect medium areas like large shops, homes, and generally all professional applications where is needed a top security technology. It is equipped with two cylinders for a very convenient, reliable and redundant shooting, shoots up to 200 m³ of dense fog in 15 seconds. It is very fast and competitive. It is prearranged to an easy wall installation and it has a lower compartment to eventually equip boards or accessories.

M³ 7200

| | GENERAL SPECIFICATIONS | |
|----|---|------------------------------|
| 2 | WEIGHT OF THE FOG MACHINE | ABOUT 11 KG |
| | WEIGHT WITH PACKAGING | ABOUT 13 KG |
| | UNITS ON ONE PALLET 100X120 | 24 |
| | DIMENSION OF THE MACHINE | 27,5X23,0Xh44,0 |
| 1 | DIMENSION OF THE PACKAGING | 37,0X25,0XH47,0 |
| 10 | COLORS | WHITE |
| | WORKING TIME WITHOUT MAINS POWER | ABOUT 2 HOURS |
| | HEAT UP TIME FROM COLD | ABOUT 70 MINUTES |
| | VERTICAL OR CORNER MOUNTING | YES |
| | HORIZONTAL MOUNTING | YES |
| | SERIAL USB PORT FOR MONITORING | YES |
| | NOZZLE TAMPER | YES |
| | SERIAL BUS FOR STANDARD PROTOCOL | YES |
| | ALARM KIT | OPTIONAL |
| | FOG GENERATOR | |
| Q | NEW HEATING SYSTEM PLUS | YES |
| | MAX FOG SINGLE SHOT (1,5 M VISIBILITY) | UP TO 300 m ³ |
| 1 | MAX FOG SINGLE SHOT (RECOMMENDED DENSIT | Y) UP TO 200 m ³ |
| ٠ | MAX SECONDS OF FOG EMISSSION | 15 sec |
| | MAX FOG EMITTED WITH FULL FOG TANK | 1800 m ³ |
| | NUMBER OF CYLINDERS | 2 |
| | FOG TANK CAPACITY | 2 x 600 ml |
| | SHOOTING SPECIFICATION | PROGRAMMABLE IN SECONDS |
| 1 | CYLINDER MODEL | VERTICAL / HORIZONTAL |
| | CYLINDER INCLUDED | 2 |
| 2 | DOUBLE FOG TANK ADVANTAGE | YES |
| r | ELECTRICAL SPECIFICATIONS | |
| - | POWER SUPPLY | 220 V or 110 V |
| C | AVERAGE POWER CONSUMPTION | 37 W |
| - | BACK UP BATTERY | YES |
| | OPTIONAL DEMO/ANTIROBBERY KIT | YES |
| | INPUTS WIRED ARMING AND SHOOTING | YES |
| | OUTPUTS WIRED | YES |
| | STANDARD COMMUNICATION PROTOCOL | YES |
| | STANDARDS | |
| | COMPLIES WITH EUROPEAN CE | YES |
| | FOG FLUID IS CERTIFIED | YES |
| | MEETS EUROPEAN STANDARD | YES |
| | | |

Powerful and fast fogging system, can cover up to 200 m³ each shot.

The densest fog among all the fogging systems thanks to 80% of glycol in its fog fluid and the proprietary shooting technology.

Patented double fog cylinder is the best solution to shoot fog, tanks are easy to change and disposable. When the first cylinder is empty the machine switches automatically to the second one even during the same shot.

Thanks to the massive insulation UR FOG fogging systems have a very low power consumption and can shoot for a long time in absence of mains power; temperature is constantly stable.

Another exclusive, patented and very useful plus that allows to detect automatically if the nozzle is tampered and sends an advise signal.

A unique serial bus to plug on the electronic board an add on card that allows to easily interface the machine with alarms and to control the fogging system even from remote. A standard protocol is available for all machines.

UR FOG fogging systems are innovative in their technology and performances, in order to guarantee the most effective protection against thefts and they have different patents.

UR FOG fogging systems are certified after European regulation. Fog fluid is assessed as not dangerous for people and animals and does not leave residuals.







mª ANI

PORT

VUSB (5V)

FAST 02 2C PRO PLUS

UR FOG

0

20

It is the ideal fogging system to protect medium areas like large shops, homes, and generally all professional applications where is needed a top security technology. It is equipped with two cylinders for a very convenient, reliable and redundant shooting, shoots up to 400 m³ of dense fog in 25 seconds. It is very fast and competitive. It is prearranged to an easy wall installation and it has a lower compartment to eventually equip boards or accessories.

| | GENERAL SPECIFICATIONS | |
|----|---|------------------------------|
| 2 | WEIGHT OF THE FOG MACHINE | ABOUT 15 KG |
| | WEIGHT WITH PACKAGING | ABOUT 18 KG |
| | UNITS ON ONE PALLET 100X120 | 24 |
| | DIMENSION OF THE MACHINE | 27,5X23,0Xh44,0 |
| 1 | DIMENSION OF THE PACKAGING | 37,0X25,0XH47,0 |
| 10 | COLORS | WHITE |
| | WORKING TIME WITHOUT MAINS POWER | ABOUT 2 HOURS |
| | HEAT UP TIME FROM COLD | ABOUT 90 MINUTES |
| 1 | VERTICAL OR CORNER MOUNTING | YES |
| | HORIZONTAL MOUNTING | YES |
| | SERIAL USB PORT FOR MONITORING | YES |
| | NOZZLE TAMPER | YES |
| | SERIAL BUS FOR STANDARD PROTOCOL | YES |
| | ALARM KIT | OPTIONAL |
| | FOG GENERATOR | |
| Q | NEW HEATING SYSTEM PLUS | YES |
| | MAX FOG SINGLE SHOT (1,5 M VISIBILITY) | UP TO 600 m ³ |
| 1 | MAX FOG SINGLE SHOT (RECOMMENDED DENSIT | Y) UP TO 400 m ³ |
| ٠ | MAX SECONDS OF FOG EMISSSION | 25 sec |
| | MAX FOG EMITTED WITH FULL FOG TANK | 1800 m ³ |
| | NUMBER OF CYLINDERS | 2 |
| | FOG TANK CAPACITY | 2 x 600 ml |
| | SHOOTING SPECIFICATION | PROGRAMMABLE IN SECONDS |
| | CYLINDER MODEL | VERTICAL / HORIZONTAL |
| | CYLINDER INCLUDED | 2 |
| 2 | DOUBLE FOG TANK ADVANTAGE | YES |
| ſ | ELECTRICAL SPECIFICATIONS | |
| 2 | POWER SUPPLY | 220 V or 110 V |
| ç | AVERAGE POWER CONSUMPTION | 42 W |
| - | BACK UP BATTERY | YES |
| | OPTIONAL DEMO/ANTIROBBERY KIT | YES |
| | INPUTS WIRED ARMING AND SHOOTING | YES |
| | OUTPUTS WIRED | YES |
| | STANDARD COMMUNICATION PROTOCOL | YES |
| | STANDARDS | |
| | COMPLIES WITH EUROPEAN CE | YES |
| | FOG FLUID IS CERTIFIED | YES |
| | MEETS EUROPEAN STANDARD | YES |
| | | |

MADE IN ITALY Powerful and fast fogging system, can cover up to 400 m³ each shot.

The densest fog among all the fogging systems thanks to 80% of glycol in its fog fluid and the proprietary shooting technology.

Patented double fog cylinder is the best solution to shoot fog, tanks are easy to change and disposable. When the first cylinder is empty the machine switches automatically to the second one even during the same shot.

Thanks to the massive insulation UR FOG fogging systems have a very low power consumption and can shoot for a long time in absence of mains power; temperature is constantly stable.

Another exclusive, patented and very useful plus that allows to detect automatically if the nozzle is tampered and sends an advise signal.

A unique serial bus to plug on the electronic board an add on card that allows to easily interface the machine with alarms and to control the fogging system even from remote. A standard protocol is available for all machines.

UR FOG fogging systems are innovative in their technology and performances, in order to guarantee the most effective protection against thefts and they have different patents.

UR FOG fogging systems are certified after European regulation. Fog fluid is assessed as not dangerous for people and animals and does not leave residuals.





ORTB

POR

VUSB (5V)





FAST 01 2C PRO PLUS

חק הסק

It is the most powerful machine in the market, ideal to protect large areas like big shops, warehouses, superstores or even to protect targets in open space. Shoots 1200 m³ of dense fog in 70 seconds. It is equipped with two removable fog cylinders. It is prearranged to an easy wall installation and it has a side compartment to eventually equip boards or accessories.

| | GENERAL SPECIFICATIONS | |
|----|---|------------------------------|
| | WEIGHT OF THE FOG MACHINE | ABOUT 22 KG |
| Ł | WEIGHT WITH PACKAGING | ABOUT 25 KG |
| 1 | UNITS ON ONE PALLET 100X120 | 12 |
| 6 | DIMENSION OF THE MACHINE | 30,0x35,0xh43,0 |
| J. | DIMENSION OF THE PACKAGING | 51,0X39,0XH51,2 |
| | COLORS | WHITE |
| 1 | WORKING TIME WITHOUT MAINS POWER | MORE THAN 2,5 HOURS |
| R | HEAT UP TIME FROM COLD | ABOUT 2 HOURS |
| 1 | VERTICAL OR CORNER MOUNTING | YES |
| | HORIZONTAL MOUNTING | YES |
| | SERIAL USB PORT FOR MONITORING | YES |
| 'n | NOZZLE TAMPER | YES |
| | SERIAL BUS FOR STANDARD PROTOCOL | YES |
| | ALARM KIT | OPTIONAL |
| | FOG GENERATOR | |
| | NEW HEATING SYSTEM PLUS | YES |
| V, | MAX FOG SINGLE SHOT (1,5 M VISIBILITY) | UP TO 1800 m ³ |
| 6 | MAX FOG SINGLE SHOT (RECOMMENDED DENSITY | Y) UP TO 1200 m ³ |
| 2 | MAX SECONDS OF FOG EMISSSION | 70 sec |
| | MAX FOG EMITTED WITH FULL FOG TANK | 1800 m ³ |
| 2 | NUMBER OF CYLINDERS | 2 |
| | FOG TANK CAPACITY | 2 x 600 ml |
| | SHOOTING SPECIFICATION | PROGRAMMABLE IN SECONDS |
| | CYLINDER MODEL | VERTICAL / HORIZONTAL |
| | CYLINDER INCLUDED | 2 |
| | DOUBLE FOG TANK ADVANTAGE | YES |
| - | ELECTRICAL SPECIFICATIONS | |
| đ | POWER SUPPLY | 220V or 110V |
| | AVERAGE POWER CONSUMPTION | 60 W |
| 1 | BACK UP BATTERY | YES |
| | OPTIONAL DEMO/ANTIROBBERY KIT | YES |
| | INPUTS WIRED ARMING AND SHOOTING | YES |
| | OUTPUTS WIRED | YES |
| C | STANDARD COMMUNICATION PROTOCOL | YES |
| ב | STANDARDS | |
| P | COMPLIES WITH EUROPEAN CE | YES |
| | FOG FLUID IS CERTIFIED MEETS EUROPEAN STANDARD | YES |
| | MEETS EUROPEAN STANDARD | YES |

MADE IN ITALY PRODUCT

C

The fastest and most powerful machines shooting up to 1200 m³ in 70 seconds.

The densest fog among all the fogging systems thanks to 80% of glycol in its fog fluid and the proprietary shooting technology.

Patented double fog cylinder is the best solution to shoot fog, tanks are easy to change and disposable. When the first cylinder is empty the machine switches automatically to the second one even during the same shot.

Thanks to the massive insulation UR FOG fogging systems have a very low power consumption and can shoot for a long time in absence of mains power; temperature is constantly stable.

Another exclusive, patented and very useful plus that allows to detect automatically if the nozzle is tampered and sends an advise signal.

A unique serial bus to plug on the electronic board an add on card that allows to easily interface the machine with alarms and to control the fogging system even from remote. A standard protocol is available for all machines.

UR FOG fogging systems are innovative in their technology and performances, in order to guarantee the most effective protection against thefts and they have different patents.

UR FOG fogging systems are certified after European regulation. Fog fluid is assessed as not dangerous for people and animals and does not leave residuals.





IΡ

PORT

œ

New generation fogging systems with pump technology and bag. Powerful and fast machines, they can protect small and large areas as they cover volume spaces from 200 m³ to 4000 m³ based on the model.





PLUS ELECTRONIC BOARD THAT EQUIPS PUMP PRO PLUS FOGGING SYSTEMS

VUSB (5V)



FAST ELECTRONIC **BOARD THAT** EQUIPS FAST 03 EASY PUMP FOGGING SYSTEM

| RECHARGE | VERTICAL Horizontal | Liquid Quantity (mi) | FOG MACHINE MODEL |
|----------|------------------------|-------------------------|---|
| | VERTICAL HORIZONTAL | 500 | Fast 03 EASY PUMP |
| | VERTICAL HORIZONTAL | 1000 | Fast 250 PUMP PRO PLUS Fast 500 PUMP PRO PLUS Fast 1500 PUMP PRO PLUS |
| WHITE | VERTICAL | 4000 | Fast 4000 PUMP PRO PLUS |

£.

PRO PLUS

ORT



NEW FOG STORM PUMP THAT EQUIPS PUMP PRO PLUS FOGGING SYSTEMS



FIXED NOZZLE THAT EQUIPS FAST 03 EASY PUMP FOGGING SYSTEM



ADJUSTABLE NOZZLE THAT EQUIPS PUMP PRO PLUS FOGGING SYSTEM



STANDARD PUMP THAT EQUIPS FAST 03 EASY PUMP FOGGING SYSTEM



BATTERY PACK **INSTALLED IN** FAST 03 EASY PUMP FOGGING SYSTEM



POWER SUPPLY AND 2Ah BATTERY INSTALLED IN PUMP PRO PLUS FOGGING SYSTEMS (BATTERY NOT INCLUDED)



PORT

VUSB (5V)



m³ 200

FAST 03 EASY PUMP

It is the ideal fogging system to protect small areas like shops, homes, garages. When the machine is triggered it shoots for the seconds set, when the bag is empty you just replace it with a new one in a very easy way. The fluid bag covers 200 m³ in 35 seconds. The price of Fast 03 Pump is the most aggressive on the market but its performances are comparable to a top professional machine as speed of fog ejection.

| GENERAL SPECIFICATIONS | |
|--|-----------------------------|
| WEIGHT OF THE FOG MACHINE | ABOUT 9 KG |
| WEIGHT WITH PACKAGING | ABOUT 11 KG |
| UNITS ON ONE PALLET 100X120 | 30 |
| DIMENSION OF THE MACHINE | 26,5X19,0XH34,5 |
| DIMENSION OF THE PACKAGING | 32,0X25,0XH43,0 |
| COLORS | BLACK/WHITE |
| WORKING TIME WITHOUT MAINS POWER | ABOUT 2 HOURS |
| HEAT UP TIME FROM COLD | ABOUT 70 MINUTES |
| VERTICAL OR CORNER MOUNTING | YES |
| HORIZONTAL MOUNTING | YES |
| SERIAL USB PORT FOR MONITORING | YES |
| NOZZLE TAMPER | NO |
| SERIAL BUS FOR STANDARD PROTOCOL | YES |
| ALARM KIT | OPTIONAL |
| FOG GENERATOR | |
| NEW HEATING SYSTEM PLUS | YES |
| MAX FOG SINGLE SHOT (1,5 M VISIBILITY) | UP TO 300 m ³ |
| MAX FOG SINGLE SHOT (RECOMMENDED DENSITY | ') UP TO 200 m ³ |
| MAX SECONDS OF FOG EMISSION | 35 sec |
| MAX FOG EMITTED WITH FULL FOG BAG | 750 m ³ |
| NUMBER OF BAG | 1 |
| FOG TANK CAPACITY | 1 x 500 ml |
| SHOOTING SPECIFICATION | PROGRAMMABLE IN SECONDS |
| BAG INCLUDED | 1 |
| ELECTRICAL SPECIFICATIONS | |
| POWER SUPPLY | 220 V or 110 V |
| AVERAGE POWER CONSUMPTION | 37 W |
| BACK UP BATTERY | YES |
| STANDARDS | |
| COMPLIES WITH EUROPEAN CE | YES |
| FOG FLUID IS CERTIFIED | YES |
| MEETS EUROPEAN STANDARD | YES |
| | |

Powerful and fast fogging system, can cover up to 200 m³ in 35 seconds.

The densest fog among all the fogging systems thanks to 80% of glycol in its fog fluid and the proprietary shooting technology.

It is very easy to change and with a very competitive price.

Thanks to the massive insulation UR FOG fogging systems have a very low power consumption and can shoot for a long time in absence of mains power; temperature is constantly stable.

A unique serial bus to plug on the electronic board an add on card that allows to easily interface the machine with alarms and to control the fogging system even from remote. A standard protocol is available for all machines.

UR FOG fogging systems are innovative in their technology and performances, in order to guarantee the most effective protection against thefts and they have different patents.

UR FOG fogging systems are certified after European regulation. Fog fluid is assessed as not dangerous for people and animals and does not leave residuals.

ORI



ORTB





FAST 250 PUMP PRO PLUS

UR FOG

ac

It is the ideal fogging system to protect small /medium areas like shops, homes, garages. When the machine is triggered it shoots for the seconds set, when the bag is empty you just replace it with a new one in a very easy way. The fluid bag covers 250 m³ in 30 seconds. It is prearranged to an easy wall installation and it has a lower compartment to eventually equip boards or accessories.

| GENERAL SPECIFICATIONS | |
|---|--|
| GENERAL SPECIFICATIONS WEIGHT OF THE FOG MACHINE WEIGHT WITH PACKAGING UNITS ON ONE PALLET 100X120 DIMENSION OF THE MACHINE DIMENSION OF THE PACKAGING COLORS WORKING TIME WITHOUT MAINS POWER HEAT UP TIME FROM COLD VERTICAL OR CORNER MOUNTING HORIZONTAL MOUNTING SERIAL USB PORT FOR MONITORING NOZZLE TAMPER SERIAL BUS FOR STANDARD PROTOCOL ALARM KIT | ABOUT 14 KG ABOUT 15 KG 24 23,0X27,0XH34,0 26,0X38,0XH53,0 WHITE ABOUT 2 HOURS ABOUT 70 MINUTES YES YES YES YES YES YES YES YES |
| FOG GENERATOR | OPTIONAL |
| NEW HEATING SYSTEM PLUS MAX FOG SINGLE SHOT (1,5 M VISIBILITY) MAX FOG SINGLE SHOT (RECOMMENDED DENSITY MAX SECONDS OF FOG EMISSION MAX FOG EMITTED WITH FULL FOG BAG NUMBER OF BAG FOG TANK CAPACITY SHOOTING SPECIFICATION BAG INCLUDED | YES UP TO 300 m ³ () UP TO 250 m ³ 30 sec 1500 m ³ 1 1x 1000 ml PROGRAMMABLE IN SECONDS 1 |
| ELECTRICAL SPECIFICATIONS | |
| POWER SUPPLY AVERAGE POWER CONSUMPTION BACK UP BATTERY PIR SENSOR VALIDATION INPUT SHOT CONFIRMATION OUTPUT POWER SUPPLY 2AH BATTERY | 220 V or 110 V 37 W YES YES YES YES YES |
| STANDARDS | |
| COMPLIES WITH EUROPEAN CE FOG FLUID IS CERTIFIED MEETS EUROPEAN STANDARD | YES YES YES |

MADE IN ITALY PRODUCT Powerful and fast fogging system, can cover up to 250 $\rm m^3$ in 30 seconds.

The densest fog among all the fogging systems thanks to 80% of glycol in its fog fluid and the proprietary shooting technology.

It is very easy to change and with a very competitive price.

Thanks to the massive insulation UR FOG fogging systems have a very low power consumption and can shoot for a long time in absence of mains power; temperature is constantly stable.

Another exclusive, patented and very useful plus that allows to detect automatically if the nozzle is tampered and sends an advise signal.

A unique serial bus to plug on the electronic board an add on card that allows to easily interface the machine with alarms and to control the fogging system even from remote. A standard protocol is available for all machines.

UR FOG fogging systems are innovative in their technology and performances, in order to guarantee the most effective protection against thefts and they have different patents.

UR FOG fogging systems are certified after European regulation. Fog fluid is assessed as not dangerous for people and animals and does not leave residuals.





ORT B

PORT

VUSB (5V)







FAST 500 PUMP PRO PLUS

UR FOG

It is a powerful and fast fogging system, ideal to protect small and medium areas like shops, homes, bank ATM machines and generally all professional applications where a top is needed security technology. It is equipped with one fog bag for a very convenient, reliable and redundant shooting, shoots up to 500 m³ of dense fog in 30 seconds. It is prearranged to an easy wall installation and it has a lower compartment to eventually equip boards or accessories.

m³ 500

| GENERAL SPECIFICATIONS | |
|---|-------------------------------|
| WEIGHT OF THE FOG MACHINE | ABOUT 17 KG |
| WEIGHT WITH PACKAGING | ABOUT 18 KG |
| UNITS ON ONE PALLET 100X120 | 24 |
| DIMENSION OF THE MACHINE | 23,0X27,0XH34,0 |
| DIMENSION OF THE PACKAGING | 26,0X38,0XH53,0 |
| COLORS | WHITE |
| WORKING TIME WITHOUT MAINS POWER | ABOUT 2 HOURS |
| HEAT UP TIME FROM COLD | ABOUT 70 MINUTES |
| VERTICAL OR CORNER MOUNTING | YES |
| HORIZONTAL MOUNTING SERIAL USB PORT FOR MONITORING | YES YES |
| NOZZLE TAMPER | YES |
| SERIAL BUS FOR STANDARD PROTOCOL | YES |
| ALARM KIT | OPTIONAL |
| FOG GENERATOR | OFHORAL |
| NEW HEATING SYSTEM PLUS | YES |
| MAX FOG SINGLE SHOT (1,5 M VISIBILITY) | UP TO 750 m ³ |
| MAX FOG SINGLE SHOT (RECOMMENDED DENSIT | (TY) UP TO 500 m ³ |
| MAX SECONDS OF FOG EMISSION | 30 sec |
| MAX FOG EMITTED WITH FULL FOG BAG | 1500 m ³ |
| NUMBER OF BAG | 1 |
| FOG TANK CAPACITY | 1 x 1000 ml |
| SHOOTING SPECIFICATION | PROGRAMMABLE IN SECONDS |
| BAG INCLUDED | 1 |
| ELECTRICAL SPECIFICATIONS POWER SUPPLY | 000 M |
| AVERAGE POWER CONSUMPTION | 220 V or 110 V 42 W |
| BACK UP BATTERY | 42 W YES |
| PIR SENSOR VALIDATION INPUT | YES |
| SHOT CONFIRMATION OUTPUT | YES |
| POWER SUPPLY | YES |
| 2AH BATTERY | YES |
| STANDARDS | |
| COMPLIES WITH EUROPEAN CE | YES |
| FOG FLUID IS CERTIFIED | YES |
| MEETS EUROPEAN STANDARD | YES |

Powerful and fast fogging system, can cover up to 500 m³ in 30 seconds.

The densest fog among all the fogging systems thanks to 80% of glycol in its fog fluid and the proprietary shooting technology.

It is very easy to change and with a very competitive price.

Thanks to the massive insulation UR FOG fogging systems have a very low power consumption and can shoot for a long time in absence of mains power; temperature is constantly stable.

Another exclusive, patented and very useful plus that allows to detect automatically if the nozzle is tampered and sends an advise signal.

A unique serial bus to plug on the electronic board an add on card that allows to easily interface the machine with alarms and to control the fogging system even from remote. A standard protocol is available for all machines.

UR FOG fogging systems are innovative in their technology and performances, in order to guarantee the most effective protection against thefts and they have different patents.

UR FOG fogging systems are certified after European regulation. Fog fluid is assessed as not dangerous for people and animals and does not leave residuals.





PORT

VUSB (5V)

JR FOG







FAST 1500 PUMP PRO PLUS

It is a powerful and fast fogging system, ideal to protect large areas like big shops, warehouses, superstores or even to protect targets in open space. It is equipped with one fog bag for a very convenient, reliable and redundant shooting, shoots up to 1500 m³ of dense fog in 70 seconds. It is prearranged to an easy wall installation and it has a side compartment to eventually equip boards or accessories.

m³ 1500

| GENERAL SPECIFICATIONS | |
|---|---------------------------|
| WEIGHT OF THE FOG MACHINE | ABOUT 22 KG |
| WEIGHT WITH PACKAGING | ABOUT 25 KG |
| UNITS ON ONE PALLET 100X120 | 12 |
| DIMENSION OF THE MACHINE | 30,0X34,5XH42,5 |
| DIMENSION OF THE PACKAGING | 51,0X39,0XH52,5 |
| COLORS | WHITE |
| WORKING TIME WITHOUT MAINS POWER | OVER 2,5 HOURS |
| HEAT UP TIME FROM COLD | ABOUT 2 HOURS |
| VERTICAL OR CORNER MOUNTING | YES |
| HORIZONTAL MOUNTING | YES |
| SERIAL USB PORT FOR MONITORING | YES YES |
| NOZZLE TAMPER SERIAL BUS FOR STANDARD PROTOCOL | YES |
| ALARM KIT | OPTIONAL |
| FOG GENERATOR | OPTIONAL |
| NEW HEATING SYSTEM PLUS | YES |
| MAX FOG SINGLE SHOT (1,5 M VISIBILITY) | UP TO 2000 m ³ |
| MAX FOG SINGLE SHOT (RECOMMENDED DENSITY | |
| MAX SECONDS OF FOG EMISSION | 70 sec |
| MAX FOG EMITTED WITH FULL FOG BAG | 1500 m ³ |
| NUMBER OF BAG | 1 |
| FOG TANK CAPACITY | 1 x 1000 ml |
| SHOOTING SPECIFICATION | PROGRAMMABLE IN SECONDS |
| BAG INCLUDED | 1 |
| ELECTRICAL SPECIFICATIONS | |
| POWER SUPPLY | 220 V or 110 V |
| AVERAGE POWER CONSUMPTION | 60 W |
| BACK UP BATTERY | YES |
| PIR SENSOR VALIDATION INPUT | YES |
| SHOT CONFIRMATION OUTPUT | YES |
| POWER SUPPLY | YES |
| 2AH BATTERY | YES |
| STANDARDS COMPLIES WITH EUROPEAN CE | YES |
| FOG FLUID IS CERTIFIED | YES |
| MEETS EUROPEAN STANDARD | YES |
| WELTO LONOF LAW STANDARD | 1ES |

Powerful and fast fogging system, can cover up to 1500 m³ in 70 seconds.

The densest fog among all the fogging systems thanks to 80% of glycol in its fog fluid and the proprietary shooting technology.

It is very easy to change and with a very competitive price.

Thanks to the massive insulation UR FOG fogging systems have a very low power consumption and can shoot for a long time in absence of mains power; temperature is constantly stable.

Another exclusive, patented and very useful plus that allows to detect automatically if the nozzle is tampered and sends an advise signal.

A unique serial bus to plug on the electronic board an add on card that allows to easily interface the machine with alarms and to control the fogging system even from remote. A standard protocol is available for all machines.

UR FOG fogging systems are innovative in their technology and performances, in order to guarantee the most effective protection against thefts and they have different patents.

UR FOG fogging systems are certified after European regulation. Fog fluid is assessed as not dangerous for people and animals and does not leave residuals.



0



C



M³ 4000



FAST 4000 PUMP PRO PLUS

201 אר

PORT

VUSB (5V)

It is a powerful and fast fogging system, ideal to protect large areas like big shops, warehouses, superstores or even to protect targets in open space. It is equipped with one fog bag for a very convenient, reliable and redundant shooting, shoots up to 4000 m³ of dense fog in 3 minutes. It is prearranged to an easy wall installation and it has a side compartment to eventually equip boards or accessories.

| GENERAL SPECIFICATIONS | |
|--|---------------------------|
| WEIGHT OF THE FOG MACHINE | ABOUT 46 KG |
| WEIGHT WITH PACKAGING | ABOUT 49 KG |
| UNITS ON ONE PALLET 100X120 | 4 |
| DIMENSION OF THE MACHINE | 45,0X31,0XH45,0 |
| DIMENSION OF THE PACKAGING | 61,0X49,0XH62,5 |
| COLORS | WHITE |
| WORKING TIME WITHOUT MAINS POWER | ABOUT 5 HOURS |
| HEAT UP TIME FROM COLD | ABOUT 8 HOURS |
| VERTICAL MOUNTING | YES, BRACKET INCLUDED |
| HORIZONTAL / CORNER MOUNTING | NO |
| SERIAL USB PORT FOR MONITORING | YES |
| NOZZLE TAMPER | YES |
| SERIAL BUS FOR STANDARD PROTOCOL | YES |
| ALARM KIT | OPTIONAL |
| FOG GENERATOR | |
| NEW HEATING SYSTEM PLUS | YES |
| MAX FOG SINGLE SHOT (1,5 M VISIBILITY) | UP TO 6000 m ³ |
| MAX FOG SINGLE SHOT (RECOMMENDED DENSITY | , |
| MAX SECONDS OF FOG EMISSION | 3 min. |
| MAX FOG EMITTED WITH FULL FOG BAG | 6000 m ³ |
| NUMBER OF BAG | 1 |
| FOG TANK CAPACITY | 1 x 4000 ml |
| SHOOTING SPECIFICATION | PROGRAMMABLE IN SECONDS |
| BAG INCLUDED | 1 |
| ELECTRICAL SPECIFICATIONS | |
| POWER SUPPLY | 220 V or 110 V |
| AVERAGE POWER CONSUMPTION | 80 W |
| BACK UP BATTERY | YES |
| PIR SENSOR VALIDATION INPUT | YES |
| SHOT CONFIRMATION OUTPUT | YES |
| POWER SUPPLY | YES |
| 2AH BATTERY | YES |
| STANDARDS | |
| COMPLIES WITH EUROPEAN CE | YES |
| FOG FLUID IS CERTIFIED | YES |
| MEETS EUROPEAN STANDARD | YES |
| | |

Wall bracket included for an easy installation and handles recommended for transport

Powerful and fast fogging system, can cover up to 4000 $m^{\rm 3}$ in 3 minutes.

The densest fog among all the fogging systems thanks to 80% of glycol in its fog fluid and the proprietary shooting technology.

It is very easy to change and with a very competitive price.

Thanks to the massive insulation UR FOG fogging systems have a very low power consumption and can shoot for a long time in absence of mains power; temperature is constantly stable.

Another exclusive, patented and very useful plus that allows to detect automatically if the nozzle is tampered and sends an advise signal.

A unique serial bus to plug on the electronic board an add on card that allows to easily interface the machine with alarms and to control the fogging system even from remote. A standard protocol is available for all machines.



C

UR FOG fogging systems are certified after European regulation. Fog fluid is assessed as not dangerous for people and animals and does not leave residuals.



UR FOG fogging systems are innovative in their technology and performances, in order to guarantee the most effective protection against thefts and they have different patents.





ELLIPSE LINE

œ

A

R

New line of fog machines with round design, powerful and fast, they use pump technology and bag. They are able to protect small and large areas as they cover volume spaces from 200 m³ to 500 m³ based on the model.





PLUS ELECTRONIC BOARD THAT EQUIPS ELLIPSE PUMP PRO PLUS FOGGING SYSTEMS



NEW FOG STORM PUMP THAT EQUIPS PUMP PRO PLUS FOGGING SYSTEMS





POWER SUPPLY AND 2Ah BATTERY INSTALLED IN ELLIPSE PUMP PRO PLUS FOGGING SYSTEMS (BATTERY NOT INCLUDED)



ORT



ADJUSTABLE NOZZLE THAT EQUIPS ELLIPSE PUMP PRO PLUS FOGGING SYSTEM





PORT

VUSB (5V)









ELLIPSE 250 PUMP PRO PLUS

It is a powerful and fast fogging system, ideal to protect small and medium areas like shops, homes, bank ATM machines and generally all professional applications where is needed a top security technology. It is equipped with one fog bag for a very convenient, reliable and redundant shooting, shoots up to 250 m³ of dense fog in 30 seconds. It is prearranged to an easy wall installation.

| GENERAL SPECIFICATIONS | |
|--|-----------------------------|
| WEIGHT OF THE FOG MACHINE | ABOUT 11 KG |
| WEIGHT WITH PACKAGING | ABOUT 13 KG |
| UNITS ON ONE PALLET 100X120 | 12 |
| DIMENSION OF THE MACHINE | 41,0X19,5XH43,0 |
| DIMENSION OF THE PACKAGING | 52,0X31,0X48.5 |
| COLORS | WHITE |
| WORKING TIME WITHOUT MAINS POWER | ABOUT 2 HOURS |
| HEAT UP TIME FROM COLD | ABOUT 70 MINUTES |
| VERTICAL MOUNTING | YES |
| HORIZONTAL MOUNTING | YES |
| SERIAL/USB PORT FOR MONITORING | YES |
| NOZZLE TAMPER | YES |
| SERIAL BUS FOR STANDARD PROTOCOL | YES |
| ALARM KIT | OPTIONAL |
| FOG GENERATOR | |
| NEW HEATING SYSTEM PLUS | YES |
| MAX FOG SINGLE SHOT (1,5 M VISIBILITY) | UP TO 300 m ³ |
| MAX FOG SINGLE SHOT (RECOMMENDED DENSIT) | () UP TO 250 m ³ |
| MAX SECONDS OF FOG IN A SINGLE SHOT | 30 sec |
| MAX FOG EMISSION WITH FULL FOG BAG | 1500 m ³ |
| NUMBER OF FOG BAGS | 1 |
| FOG BAG CAPACITY | 1 x 1000 ml |
| SHOOTING SPECIFICATION | PROGRAMMABLE IN SECONDS |
| FOG BAG INCLUDED | 1 |
| ELECTRICAL SPECIFICATIONS | |
| POWER SUPPLY | 220 V or 110 V |
| AVERAGE POWER CONSUMPTION | 37 W |
| BACK UP BATTERY | YES |
| OPTIONAL DEMO/ANTIROBBERY KIT | YES |
| WIRED INPUTS ARMING AND SHOOTING | YES |
| WIRED OUTPUTS | YES |
| STANDARD COMMUNICATION PROTOCOL | YES |
| STANDARDS | |
| COMPLIES WITH EUROPEAN CE | YES |
| FOG FLUID IS CERTIFIED | YES |
| MEETS EUROPEAN STANDARD | YES |

Powerful and fast fogging system, can cover up to 250 m^3 in 30 seconds.

The densest fog among all the fogging systems thanks to 80% of glycol in its fog fluid and the proprietary shooting technology.

It is very easy to change and with a very competitive price.

Thanks to the massive insulation UR FOG fogging systems have a very low power consumption and can shoot for a long time in absence of mains power; temperature is constantly stable.

Another exclusive, patented and very useful plus that allows to detect automatically if the nozzle is tampered and sends an advise signal.

A unique serial bus to plug on the electronic board an add on card that allows to easily interface the machine with alarms and to control the fogging system even from remote. A standard protocol is available for all machines.

UR FOG fogging systems are innovative in their technology and performances, in order to guarantee the most effective protection against thefts and they have different patents.

UR FOG fogging systems are certified after European regulation. Fog fluid is assessed as not dangerous for people and animals and does not leave residuals.



P 2





UKI B

VUSB (5V

UR FOG









ELLIPSE 500 PUMP PRO PLUS

It is a powerful and fast fogging system, ideal to protect small and medium areas like shops, homes, bank ATM machines and generally all professional applications where is needed a top security technology. It is equipped with one fog bag for a very convenient, reliable and redundant shooting, shoots up to 500 m³ of dense fog in about 30 seconds. It is prearranged to an easy wall installation.

GENERAL SPECIFICATIONS ABOUT 11 KG WEIGHT OF THE FOG MACHINE WEIGHT WITH PACKAGING ABOUT 13 KG UNITS ON ONE PALLET 100X120 12 DIMENSION OF THE MACHINE 41,0X19,5XH43,0 52,0X31,0X48.5 DIMENSION OF THE PACKAGING WHITE COLORS ABOUT 2 HOURS WORKING TIME WITHOUT MAINS POWER ABOUT 70 MINUTES HEAT UP TIME FROM COLD YES VERTICAL MOUNTING HORIZONTAL MOUNTING YES YES SERIAL/USB PORT FOR MONITORING YES NOZZLE TAMPER YES SERIAL BUS FOR STANDARD PROTOCOL OPTIONAL ALARM KIT FOG GENERATOR NEW HEATING SYSTEM PLUS YES UP TO 750 m³ MAX FOG SINGLE SHOT (1,5 M VISIBILITY) MAX FOG SINGLE SHOT (RECOMMENDED DENSITY) UP TO 500 m³ 30 sec MAX SECONDS OF FOG IN A SINGLE SHOT 1500 m³ MAX FOG EMISSION WITH FULL FOG BAG NUMBER OF FOG BAGS 1 1 x 1000 ml FOG BAG CAPACITY PROGRAMMABLE IN SECONDS SHOOTING SPECIFICATION FOG BAG INCLUDED ELECTRICAL SPECIFICATIONS 220 V or 110 V POWER SUPPLY 37 W AVERAGE POWER CONSUMPTION YES BACK UP BATTERY YES OPTIONAL DEMO/ANTIROBBERY KIT YES WIRED INPUTS ARMING AND SHOOTING YES WIRED OUTPUTS YES STANDARD COMMUNICATION PROTOCOL STANDARDS COMPLIES WITH EUROPEAN CE YES YES FOG ELUID IS CERTIFIED YES MEETS EUROPEAN STANDARD

Powerful and fast fogging system, can cover up to 500 m^3 in about 30 seconds.

The densest fog among all the fogging systems thanks to 80% of glycol in its fog fluid and the proprietary shooting technology.

It is very easy to change and with a very competitive price.

Thanks to the massive insulation UR FOG fogging systems have a very low power consumption and can shoot for a long time in absence of mains power; temperature is constantly stable.

Another exclusive, patented and very useful plus that allows to detect automatically if the nozzle is tampered and sends an advise signal.

A unique serial bus to plug on the electronic board an add on card that allows to easily interface the machine with alarms and to control the fogging system even from remote. A standard protocol is available for all machines.

UR FOG fogging systems are innovative in their technology and performances, in order to guarantee the most effective protection against thefts and they have different patents.

UR FOG fogging systems are certified after European regulation. Fog fluid is assessed as not dangerous for people and animals and does not leave residuals.





FLEX

PORT

0

66

B S D

54

The most powerful and fastest battery operated fog machine in the world with pump technology and able to cover about 750 m³. It is the ideal solution in absence of mains power. It starts shooting after one second from activation.



∭³ 750



FLEX ELECTRONIC BOARD



STANDARD PUMP

| RECHARGE | CODE | VERTICAL Horizontal | Liquid Quantity (mi) | FOG MACHINE Model | |
|----------|------|------------------------|-------------------------|----------------------|--|
| FEB | P500 | VERTICAL | 500 | FLEX | |

CAMPER



VALUE TRANSPORT



SAFES



TARGET

BOATS



ATM



MONEY EXCHANGE



CONTAINER



TRAILERS

ORT



CONSTRUCTION SITES



m³ 750

FLEX

POR

œ

PORT

VUSB (5V)

It is the most powerful and the fastest fully bat¬tery operated fogging system. Ideal to protect spaces without mains power, temporary stores, worksites, trucks, armored vans, containers, but also houses or spaces where you want to save on power consumption.

| GEI | VERAI | _ SPE(| CIFICAT | IONS | |
|-----|-------|--------|---------|------|--|
| | | | - OVOT | | |

C

| WEIGHT OF THE SYSTEM WITHOUT BATTERY | ABOUT 4,5 KG |
|--|--------------------------|
| WEIGHT WITH PACKAGING | ABOUT 5 KG |
| DIMENSION OF THE MACHINE | 25X16XH15 |
| UNITS ON A PALLET (100X120) | 48 |
| COLOR | GALVANIZED STEEL |
| WORKING TIME WITHOUT MAINS POWER | MORE THAN 3 MONTHS |
| HEAT UP TIME FROM COLD | 2 SECONDS |
| VERTICAL INSTALLATION | YES |
| HORIZONTAL INSTALLATION | NO |
| SERIAL USB PORT FOR MONITORING | YES |
| NOZZLE TAMPER | NO |
| SERIAL BUS FOR STANDARD PROTOCOL | YES |
| ALARM KIT | OPTIONAL |
| ARMING INPUT | YES |
| SHOOTING INPUT | YES |
| PIR SHOOTING VALIDATION INPUT | YES |
| EMPTY TANK OUTPUT | YES |
| TAMPER OUTPUT | YES |
| FAULT OUTPUT | YES |
| SHOOTING CONFIRMATION OUTPUT | YES |
| SPECIFICATIONS (IN STANDARD CONFIGURATION | N WITH 70 Ah BATTERY) |
| NEW HEATING SYSTEM "PLUS" | YES |
| VOLUME COVERED IN A SINGLE SHOT | UP TO 750 m ³ |
| (VISIBILITY 1,5 M, 8 MINUTES) | |
| VOLUME COVERED IN A SINGLE SHOT | UP TO 500 m ³ |
| (RECOMMENDED DENSITY, 8 MINUTES) | |
| MAXIMUM TIME OF FOG EMISSION IN A SINGLE SI | HOT ABOUT 8 min. |
| MAXIMUM FOG EMISSION WITH FULL FOG BAG | 750 m ³ |
| NUMBER OF FOG BAGS | 1 |
| FOG BAG CAPACITY | 1 x 500 ml |
| SHOOTING SPECIFICATIONS | PROGRAMMABLE IN SECONDS |
| FOG BAG INCLUDED | 1 |
| ELECTRICAL SPECIFICATIONS | |
| POWER SUPPLY | BATTERY |
| AVERAGE POWER CONSUMPTION (BATTERY) | 0,25 W |
| BACK UP BATTERY | NO |
| OPTIONAL DEMO/ANTIROBBERY KIT | |
| | YES |
| STANDARD COMMUNICATION PROTOCOL | YES YES |
| STANDARD COMMUNICATION PROTOCOL STANDARDS | |
| | |
| STANDARDS | YES |



The densest fog among all the fogging systems thanks to 80% of glycol in its fog fluid and the proprietary shooting technology.

It is very easy to change and with a very competitive price.

Just 0,25 W power consumption, can work more than 3 months only with battery.

A unique serial bus to plug on the electronic board an add on card that allows to easily interface the machine with alarms and to control the fogging system even from remote. A standard protocol is available for all machines.

UR FOG fogging systems are innovative in their technology and performances, in order to guarantee the most effective protection against thefts and they have different patents.

UR FOG fogging systems are certified after European regulation. Fog fluid is assessed as not dangerous for people and animals and does not leave residuals.









POR

0

Lan board & accessories





POR

198 O

6dr 00

VUSB (5V)

(?

Code list

| | | Fast 03 Easy 2 | F3SN220ES2 |
|-------|---------------|--|--------------|
| 6 | | Cylinder 300 ml | FESB2002 |
| | | Wall metal bracket Fast 03 Easy 2 | F03STH |
| | | Fast 03 1C | F3SN2201C |
| 10 | | Fast 03 2C | F3SN2202C |
| A CO | | Cylinder 400 ml - vertical | F3SNBOMTS |
| | i u | Cylinder 400 ml - horizontal | F3SNBOMTSOR |
| 0 | 2 | Wall metal bracket Fast 03 | F03STH |
| | | Fast 02 2C | F2SN220 |
| | FAST LINE | Cylinder 500 ml - vertical | F2SNBOM |
| 6 | <u></u> | | F2SNBOMOR |
| 122 | | Cylinder 500 ml - horizontal | |
| line. | | Wall metal braket Fast 02 | F02STH |
| | | Fast 01 2C | F1M06ITAD |
| 11 | | Cylinder 600 ml - vertical | F1M06BOM |
| | | Cylinder 600 ml - horizontal | F1M06BOMORZ |
| J | | Wall metal bracket Fast 01 | F01STH |
| PORT | | | FAONAGE |
| 2 | | Fast 03 1C Pro Plus | F3SN2201CPRO |
| | | Fast 03 2C Pro Plus | F3SN2202CPRO |
| | | Cylinder 600 ml - vertical | F1M06BOM |
| i ita | | Cylinder 600 ml - horizontal | F1M06BOMORZ |
| | PRO PLUS LINE | Wall metal bracket Fast 03 Pro Plus | F23STHPRO |
| 141 | | Fast 02 2c PRO plus | F2SN2202CPRO |
| | Ĕ | Cylinder 600 ml - vertical | F1M06BOM |
| 0 | Ē | Cylinder 600 ml - horizontal | F1M06BOMORZ |
| 100 | 2 | Wall metal bracket Fast 02 Pro Plus | F23STHPRO |
| | e . | Fast 01 2C Pro Plus | F1SN2202CPRO |
| | | Cylinder 600 ml - vertical | F1M06BOM |
| | | Cylinder 600 ml - horizontal | F1M06BOMORZ |
| 13 | | Wall metal bracket Fast 01 Pro Plus | F01STH |
| (3) | | | |
| | | Fast 03 Easy Pump | FPU03ES |
| er. | | Bag 500 ml | FFLXRC5 |
| 1-0 | | Wall metal bracket Fast 03 Easy Pump | F03STH |
| | | Fast 250 Pump Pro Plus | FPU250PP |
| | | Bag 1000 ml | FFLXRC10 |
| | <u> </u> | Wall metal bracket Fast 250 Pump Pro Plus | F23STHPRO |
| | 5 | Fast 500 Pump Pro Plus | FPU500PP |
| | e | Bag 1000 ml | FFLXRC10 |
| | PUMP LINE | Wall metal bracket Fast 500 Pump Pro Plus | F23STHPRO |
| C KO | e | Fast 1500 Pump Pro Plus | FPU1500PP |
| | | Bag 1000 ml | FFLXRC10 |
| - 2 | | Wall metal bracket Fast 1500 Pump Pro Plus | F01STH |
| | | Fast 4000 Pump Pro Plus | FPU4000PP |
| VUS | | Bag 4000 ml | FFLXRC40 |
| 1021 | | 2 Handlers Fast 4000 | FPUM |
| | | | |
| | ¥ | Ellipse 250 Pump Pro Plus | FEL250PPP |
| - | 5 | Bag 1000 ml | FFLXRC10 |
| E. | ELLIPSE LINE | Wall metal bracket Ellipse 250 Pump Pro Plus | FELSTH |
| C6 | ě, | Ellipse 500 Pump Pro Plus | FEL500PPP |
| 1 | | Bag 1000 ml | FFLXRC10 |
| | | Wall metal bracket Ellipse 500 Pump Pro Plus | FELSTH |
| UDI | | | |
| -VDI | FLEX | Flex | FFLXV1 |
| -VS | E L | Bag 500 ml | FFLXRC5 |
| | | • | |
| | | | |