

DM700KB-N

Pulsador con llave para superficie, dos posiciones. Azul.

General

The DM700KB-N is a high quality, blue plastic manual call point with key switch. It allows for on/off control of equipment such as ventilation and overrides.

The key switch has 2 positions, with the key being trapped in one position and removable in the other. Changing between these positions require the turn of the key through a 90° angle. It offers three electrical connections, which already come fitted with flying leads. One of these connections are common, while the tuning of the key result in the change over between the other two.

Construction

The robust switching device comprises a main housing and a front plate. It is fitted to the plate which simply snaps into the main housing and is permanently located in place with fixing screws. All units are supplied with 2 sturdy keys.



Detalles

- Easy to install
- High quality key switch
- Operates after long period of disuse
- Preformed mounting slots
- EN54 'burning house' functional marking
- Surface mount

DM700KB-N

Pulsador con llave para superficie, dos posiciones. Azul.

Especificaciones técnicas

Físico

Dimensiones físicas	87 x 87 x 52 mm (W x H x D)
Peso neto	166 g
Color	Azul
Tipo de Montaje	Montaje en Superficie
Marcado funcional	EN54 burning house

Medioambiental

Temperatura de funcionamiento	-20 to +55°C
Humedad relativa	0 to 90% noncondensing
Entorno	Interior
Clasificación IP	IP21

Electrical (switch specifications)

Maximum voltage	250 VAC
Maximum current	2 A @ 250 VAC
	4 A @ 125 VAC
	4 A @ 28 VDC

Productos compatibles

Categoría	Referencia	Descripción
Dispositivo de detección	DMN782	Tapa basculante de plástico para pulsadores de alarma de la serie DMN700.



Como empresa innovadora, Kidde Global Solutions se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 23 September 2025 - 16:19