

DS-PA201P-16WE Control Panel



- Simple and elegant appearance design
- Wi-Fi network for cloud communication
- Friendly app interface makes installation and use easier
- Up to 2000 m radio signal transmission range in open space

▪ Specification

Capacity	
ARC	1
Installer	1
User	14
Areas	4
Wireless zones	16
Wireless keypads	4
Wireless sounders	4
Admin	1
Wireless keyfobs	16
Logs	1000
Communication	
Transmission technology	868.0-868.6 MHz
Transmission range (free space)	up to 2,000 m
Maximum effective radiated power (ERP)	25 mW max
Radio signal modulation	2GFSK
Encryption	AES-128
Ethernet	1 8P8C socket
Ethernet speed	≤10Mbps
Wi-Fi	802.11 b/g/n
Notifications	
APP notifications	Yes
ARC notifications	Yes
Event types	Alarms Faults System Events Operations
Software features	
Upgrade OTA	Yes
Protocol	SIA-DCS *SIA-DCS ADM-CID *ADM-CID OTAP Other proprietary protocols
Indication	
Indication method	LED
Hardware features	
Tamper-Proof	Yes
Electrical characteristics	
Built-in backup battery	Yes
Battery life	Up to 12 hours at normal temperature (The battery working time can be significantly reduced at low temperatures)
Battery charging temperature	0 °C to +40 °C

General	
Dimension (W×H×D)	165 x 165 x 37.5 mm
Weight	400 g
Operation temperature	-10 °C to +55 °C
Operation humidity	10% to 90%
Shell material	Plastic

▪ Available Model

DS-PA201P-16WE

DS-PA201P-16WE(RU)

▪ Accessory

▪ Included

DS-PC201N

LAN Module



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq