

LM28-S400

28" UHD LED Monitor



Technical Specification

Model

Model	LM28-S400
-------	-----------

Display

Screen Size	28"
Aspect Ratio	16:9
Resolution	3840x2160 (UHD)
Backlight	LED
Brightness/Luminance	300cd/m ²
Contrast	1000:1
Display Color	1.07B(10bit)
Viewing Angle(H/V)	178°(H)/178°(V)
Response time	5ms
Refresh Rate	60Hz

Signals

Input	VGA(D-Sub)×1, BNC×1, DP 1.2a×1, HDMI 2.0×2, USB multimedia×1, Audio×1	
Output	BNC×1	
	Speaker	5W×2

General

Power Supply	AC100~240V (+/-10%), 50/60 Hz
--------------	-------------------------------

Features :

- 4K Ultra-HD resolution
- Industrial level LCD panel, suitable for continuous 24/7 operation
- Built-in 3D COMB filter and 3D Noise Reduction
- 5ms fast response time for no motion blur, judder or ghosting
- 1.07B colors, for a realistic and immersive visual experience
- High fidelity digital processing for a brilliant and vivid video
- Using tamper-proof metal housing
- Professional thermal design to extend equipment lifespan
- Built-in power, low energy consumption, ultra-quiet
- Wide array of connectivity options HDMI, DP, VGA, BNC, USB, Audio



Consumption (Standard)	40W	
Consumption (Standby)	≤1W	
Type	Internal	
Net Weight	6.65kg (14.7lb)	
Gross Weight	8kg (17.6lb)	
Bezel Width	19.1mm(U), 19.0mm(R/L), 27.2mm(B)	
VESA	100×100mm (3.9"×3.9")	
Dimension without standard (W×H×D)	662×390.5×50mm (26.1"×15.4"×2.0")	
Package(W×H×D)	755×490×129mm (29.7"×19.3"×5.1")	
Work Environment	Temperature	0°C~40°C (32°F~104°F)
	Humidity	10%~85%

Accessory

Standard	HDMI cable, power cable, hanging bracket
Optional	Pedestal

Certifications

Certifications	CE/FCC
----------------	--------

Dimensions(mm)

