

Model: FS-HDP4704

Features

4 Channel HD Passive Video Balun

- Real-time transmission over UTP cat5e/6
- No power required
- Compatible with all HD-TVI/CVI/AHD/CVBS analog cameras
- Please refer to "Transmission Distance Chart" Part to find out distance of 720P/960P/1080P/3MP/4MP/5MP/4K cameras
- Female BNC connector
- Built-in solid state TVS (Transient Voltage Suppressor) for surge protection
- Wave Filter Design, Anti-Static Design
- Lightning protection design Grade: III
- 60 dB crosstalk and noise immunity
- Exceptional interference rejection
- ABS engineering plastic housing



Overview

The FS-HDP4704 video balun hub is a passive (non-amplified) device that allows the transmission of real-time CCTV HD video signal via cost-effective Unshielded Twisted Paired (UTP) cable. The FS-HDP4704 is compatible with all HD-TVI, HD-CVI, AHD and CVBS analog cameras.

The FS-HDP4704 supports pluggable screw terminal or RJ45 connections. Used with single channel HD passive video transmitter, the FS-HDP4704 is capable to receive 4 channel live CCTV HD video signal from camera end via one UTP cable.

The superior interference rejection and low emissions of the FS-HDP4704 allow video signals to coexist in the same wire bundle as telephone, datacom, or low-voltage power circuits. This allows the use of a shared or existing cable plant. The FS-HDP4704 is built-in surge suppressor to protect video equipment against damaging voltage spikes and provide noise immunity to ensure quality signals without disturbing "hum-bars".

Transmission Distance Chart

Camera Type	HD-TVI	HD-CVI	HD-AHD
720P camera	250m(820ft)	440m(1443ft)	320m(1049ft)
960P camera	Not tested	Not tested	320m(1049ft)
1080P camera	250m(820ft)	250m(820ft)	250m(820ft)
3MP camera	250m(820ft)	Not tested	250m(820ft)
4MP camera	180m(590ft)	200m(656ft)	200m(656ft)
5MP camera	180m(590ft)	Not tested	180m(590ft)
4K camera	130m(426ft)	200m(656ft)	150m(492ft)
CVBS camera	400m(1312ft)		



Wire and Cable Recommendations

The FS-HDP4704 is recommended to use with Unshielded Twisted Paired (UTP) wiring from 24AWG through 22AWG. Individually shielded pairs should be avoided, as they reduce the operating range of the systems drastically. Multi-pair cable (25-pair or more) with an overall shield are acceptable. Video signals can coexist in the same wire bundle as telephone, datacom, or low-voltages power circuits. While video may be routed through telephone punch-down block terminals, any bridge-taps, also called T-taps and any resistive, capacitive or inductive devices **MUST BE** removed from the pair.

Connectable design for neat installation



splice two pieces into 8-port



splice four pieces into 16-port

Technical Specification

Model		FS-HDP4704	
Product Name		4 Channel HD Passive Video Balun	
Applied Devices		CCTV cameras, monitors, DVR, switchers, IP encoders, and other CCTV equipment	
Video	Video Format	HD-TVI/CVI/AHD/CVBS	
	Operating Frequency	DC to 71MHz	
	Common-mode/Differential-mode rejection	15KHz to 71MHz 60 dB typ.	
	Impedance	Coax: female BNC	75Ω unbalanced
		UTP: screw terminal block or RJ45 Jack	100Ω balanced
Attenuation	1.5 dB typ. Max		
Wire Type	Network Wiring	One Unshielded Twisted Pair (for each video signal) 24-16 AWG (0.5-1.31mm)	
	Category Type	2 or better	
	Impedance	100 ± 20 ohms	
	DC Loop Resistance	52 ohms per 1,000ft (18 ohms per 100m)	
	Differential Capacitance	19 pF/ft max (62 pF/m max)	
Power		No external power required	
Connector	Video input/output	Female BNC connector	
	Video output/input	pluggable screw terminal block and RJ45 for UTP (select one connection)	
Protection	Surge Protection	renewable solid state surge protection	
	Video Input	2KV (common mode), 10/700us IEC61000-4-5/1955(GB/T 1726, 5-1999)	
	Video Output	2KV (differential mode), 10/700us IEC61000-4-5/1955(GB/T 1726, 5-1999)	
	Antistatic	YES	
Mechanical	Dimensions(L*W*H)	BNC connector & mounting bracket excluded	
		180*85*32mm	
	Housing	ABS engineering plastic	
	Body Color	Black	
	Net Weight	420g	
Environmental	Operating Temperature	-20° ~ 70° C	
	Relative Humidity	0~95% (non-condensing)	
	Storage Temperature	-40° ~ 150° C	



Applications

- Security Monitoring System
- Multimedia Network Teaching System
- Medical Monitoring Display System
- Industrial Automation Control System
- Banking, securities, financial information display system
- Remote Network Server Monitoring
- Department Store Security
- Casino Security
- Hospitals, Airports and banks
- School Campuses

Application Diagram



Note:

1. The actual transmission distance will vary according to the quality of the cable, specific camera, and on-site environment.
2. Please make sure to install transmitter at camera side and receiver at DVR side to achieve the best video quality.
3. If you adjust saturation of DVR, video transmission distance could be farther. HD-CVI 720P: max up to 470m(1541ft).
4. If chromatic aberration occurs, please also adjust saturation, the picture will recover perfectly automatically.
5. The device is not waterproof and not to be used at outdoors.