

# UR FOG

The fastest fogging security systems




**FAST LINE**



# UR FOG CERTIFICATIONS

UR FOG machines have been developed, thanks to the internal R&D team and laboratories, with innovative solutions for security and fully respecting international approvals and regulations.

The fog fluid is certified by EUROFINS, one of the largest multinational companies for chemical, cosmetic, medicine certification, as not toxic for humans and animals and the fluid content is not in contrast with any Islamic country regulation. Products have been already sold in over 80 worldwide countries.



Fogging machines have EMC - FCC - CE approvals and respect EN 50131-8 regulation.



# UR FOG PRODUCT RANGE

**FAST 03 EASY 2** *m<sup>3</sup> 200*

Up to 200 m<sup>3</sup> (recommended visibility)  
One cylinder 300 ml included  
Shoots full cylinder in two times  
Vertical installation  
Adjustable nozzle  
TWO INPUTS: arming, shooting  
THREE OUTPUTS: empty cylinder, fault, anti-tampering door

**FAST 03 1C** *m<sup>3</sup> 200*

Up to 200 m<sup>3</sup> (recommended visibility)  
One cylinder 400 ml included  
Shoots programmable in seconds  
Vertical/horizontal installation  
Adjustable nozzle  
TWO INPUTS: arming, shooting  
THREE OUTPUTS: empty cylinder, fault, anti-tampering

**FAST 03 2C** *m<sup>3</sup> 200*

Up to 200 m<sup>3</sup> (recommended visibility)  
Two cylinders 400 ml included  
Shoots programmable in seconds  
Vertical/horizontal installation  
Adjustable nozzle  
TWO INPUTS: arming, shooting  
THREE OUTPUTS: empty cylinder, fault, anti-tampering

**FAST 02 2C** *m<sup>3</sup> 400*

Up to 400 m<sup>3</sup> (recommended visibility)  
Two cylinders 500 ml included  
Shoots programmable in seconds  
Vertical/horizontal installation  
Adjustable nozzle  
TWO INPUTS: arming, shooting  
THREE OUTPUTS: empty cylinder, fault, anti-tampering

**FAST 01 2C** *m<sup>3</sup> 1200*

Up to 1200 m<sup>3</sup> (recommended visibility)  
Two cylinders 600 ml included  
Shoots programmable in seconds  
Vertical/horizontal installation  
Adjustable nozzle  
TWO INPUTS: arming, shooting  
THREE OUTPUTS: empty cylinder, fault, anti-tampering


## TECHNICAL LIST

### FAST LINE

	FAST 03 EASY 2	FAST 03 1C	FAST 03 2C	FAST 02 2C	FAST 01 2C
MAX FOG EMISSION IN A SINGLE SHOT	200 m <sup>3</sup>	200 m <sup>3</sup>	200 m <sup>3</sup>	400 m <sup>3</sup>	1200 m <sup>3</sup>
MAX SECONDS IN A SINGLE SHOT	15 sec	15 sec	15 sec	25 sec	70 sec
TOTAL EMISSION WITH FULL FOG TANKS	400 m <sup>3</sup>	600 m <sup>3</sup>	1200 m <sup>3</sup>	1500 m <sup>3</sup>	1800 m <sup>3</sup>
CYLINDERS OR PUMP	1 CYLINDER	1 CYLINDER	2 CYLINDERS	2 CYLINDERS	2 CYLINDERS
FOG TANK CAPACITY	300 ml	400 ml	400 ml	500 ml	600 ml
WORKING TIME WITHOUT MAINS POWER	ABOUT 2 H	ABOUT 2 H	ABOUT 2 H	ABOUT 2 H	OVER 2,5 H
HEATING TIME	ABOUT 70 min.	ABOUT 70 min.	ABOUT 70 min.	ABOUT 90 min.	ABOUT 2 H
VERTICAL/CORNER MOUNTING	BOTH	BOTH	BOTH	BOTH	VERTICAL
HORIZONTAL MOUNTING	NO	YES	YES	YES	OPT.
SERIAL PORT FOR BUS	YES	YES	YES	YES	YES
AVERAGE POWER CONSUMPTION	37 W	37 W	37 W	42 W	60 W
BACK UP BATTERY OPT.	6 ALCALINE BATTERIES	6 ALCALINE BATTERIES	6 ALCALINE BATTERIES	6 ALCALINE BATTERIES	6 ALCALINE BATTERIES
ELECTRONIC BOARD	FAST	FAST	FAST	FAST	FAST
CABINET TYPE	FAST	FAST	FAST	FAST	FAST
FOG FLUID CERTIFIED AS NOT DANGEROUS	YES	YES	YES	YES	YES
EUROPEAN STANDARD CERTIFICATIONS	YES	YES	YES	YES	YES
HEATER CARTRIDGE	300 W	300 W	300 W	300 W	600 W


# UR fog FAST LINE

Fog machines able to protect small and large areas as they cover volume spaces from 200 m<sup>3</sup> to 1200 m<sup>3</sup> based on the model. Cylinder shot technology, professional and really price aggressive line.



The ideal protection for small and medium areas where the instantaneity of the fog saturation is key feature. The patented cylinder technology allows the systems to operate even in case of a tampering condition, in particular inside small environments where the fogging security system is easily accessible. The devices interface with any alarm station by sending diagnostic information.

RECHARGE	VERTICAL HORIZONTAL	LIQUID QUANTITY (ml)	FOG MACHINE MODEL
	VERTICAL	300	FAST 03 EASY 2
	VERTICAL HORIZONTAL	400	FAST 03 1C FAST 03 2C
	VERTICAL HORIZONTAL	500	FAST 02 2C
	VERTICAL HORIZONTAL	600	FAST 01 2C



FAST ELECTRONIC BOARD



BATTERY PACK



ADJUSTABLE NOZZLE



EASY TO CHANGE CYLINDER



## FAST 03 EASY 2

It is the ideal fogging system to protect small or medium areas like shops, homes, garages. The machine shoots the cylinder content in two times, then you just replace it with a new one in a very easy way. Each shot covers 200 m<sup>3</sup> in 15 seconds. The price of Fast 03 Easy 2 is the most aggressive in the market but its performances are comparable to a top professional machine as speed of fog ejection.

### GENERAL SPECIFICATIONS

WEIGHT OF THE FOG MACHINE	ABOUT 10 KG
WEIGHT WITH PACKAGING	ABOUT 11 KG
UNITS ON ONE PALLET 100X120	36
DIMENSION OF THE MACHINE	26,5X23,0XH34,5
DIMENSION OF THE PACKAGING	32,0X25,0XH43,0
COLORS	WHITE
WORKING TIME WITHOUT MAINS POWER	ABOUT 2 HOURS
HEAT UP TIME FROM COLD	ABOUT 70 MINUTES
VERTICAL OR CORNER MOUNTING	YES
HORIZONTAL MOUNTING	NO
SERIAL USB PORT FOR MONITORING	YES
NOZZLE TAMPER	NO
SERIAL BUS FOR STANDARD PROTOCOL	YES
ALARM KIT	OPTIONAL

### FOG GENERATOR

NEW HEATING SYSTEM PLUS	YES
COVERAGE IN A SINGLE SHOT (1,5 M VISIBILITY)	UP TO 300 m <sup>3</sup>
COVERAGE IN A SINGLE SHOT (RECOMMENDED DENSITY)	UP TO 200 m <sup>3</sup>
MAX SECONDS OF FOG EMISSION	15 sec
MAX FOG EMITTED WITH FULL FOG TANK	400 m <sup>3</sup>
NUMBER OF CYLINDERS	1
FOG TANK CAPACITY	1x 300 ml
SHOOTING SPECIFICATION	2 SHOTS (200 m <sup>3</sup> EACH)
CYLINDER MODEL	VERTICAL
CYLINDER INCLUDED	1

### ELECTRICAL SPECIFICATIONS

POWER SUPPLY	230 V or 110 V
AVERAGE POWER CONSUMPTION	37 W
BATTERY PACK	YES
ANTIROBBERY KIT	YES
WIRED INPUTS ARMING AND SHOOTING	YES
WIRED OUTPUTS	YES
STANDARD COMMUNICATION PROTOCOL	YES

### STANDARDS

COMPLIES WITH EUROPEAN CE	YES
FOG FLUID IS CERTIFIED	YES
MEETS EUROPEAN STANDARD	YES



Powerful and fast fogging system, can cover up to 200 m<sup>3</sup> each shot.



The densest fog among all the fogging systems thanks to 80% of glycol in its fog fluid and the proprietary shooting technology.



Removable and disposable fog cylinder, very easy to change and with a very competitive price.



Thanks to the massive insulation UR FOG fogging systems have a very low power consumption and can shoot for a long time in absence of mains power; temperature is constantly stable.



A unique serial bus to plug on the electronic board an add on card that allows to easily interface the machine with alarms and to control the fogging system even from remote. A standard protocol is available for all machines.



UR FOG fogging systems are innovative in their technology and performances, in order to guarantee the most effective protection against thefts and they have different patents.



UR FOG fogging systems are certified after European regulation. Fog fluid is assessed as not dangerous for people and animals and does not leave residuals.



m<sup>3</sup> 200

### FAST 03 1C

It is the ideal fogging system to protect small and medium areas like shops, homes, bank ATM machines. It is the entry level of the professional line, shoots up to 200 m<sup>3</sup> of dense fog in 15 seconds. It is equipped with a single cylinder and shooting time can be set in seconds. It is very fast and competitive.



Powerful and fast fogging system, can cover up to 200 m<sup>3</sup> in 15 seconds.



The densest fog among all the fogging systems thanks to 80% of glycol in its fog fluid and the proprietary shooting technology.



Removable and disposable fog cylinder, very easy to change and with a very competitive price.



Thanks to the massive insulation UR FOG fogging systems have a very low power consumption and can shoot for a long time in absence of mains power; temperature is constantly stable.



A unique serial bus to plug on the electronic board an add on card that allows to easily interface the machine with alarms and to control the fogging system even from remote. A standard protocol is available for all machines.



UR FOG fogging systems are innovative in their technology and performances, in order to guarantee the most effective protection against thefts and they have different patents.



UR FOG fogging systems are certified after European regulation. Fog fluid is assessed as not dangerous for people and animals and does not leave residuals.

#### GENERAL SPECIFICATIONS

WEIGHT OF THE FOG MACHINE	ABOUT 10 KG
WEIGHT WITH PACKAGING	ABOUT 11 KG
UNITS ON ONE PALLET 100X120	36
DIMENSION OF THE MACHINE	26,5X23,0XH34,5
DIMENSION OF THE PACKAGING	32,0X25,0XH43,0
COLORS	WHITE
WORKING TIME WITHOUT MAINS POWER	ABOUT 2 HOURS
HEAT UP TIME FROM COLD	ABOUT 70 MINUTES
VERTICAL OR CORNER MOUNTING	YES
HORIZONTAL MOUNTING	YES
SERIAL USB PORT FOR MONITORING	YES
NOZZLE TAMPER	YES
SERIAL BUS FOR STANDARD PROTOCOL	YES
ALARM KIT	OPTIONAL

#### FOG GENERATOR

NEW HEATING SYSTEM PLUS	YES
COVERAGE IN A SINGLE SHOT (1,5 M VISIBILITY)	UP TO 300 m <sup>3</sup>
COVERAGE IN A SINGLE SHOT (RECOMMENDED DENSITY)	UP TO 200 m <sup>3</sup>
MAX SECONDS OF FOG EMISSION	15 sec
MAX FOG EMITTED WITH FULL FOG TANK	600 m <sup>3</sup>
NUMBER OF CYLINDERS	1
FOG TANK CAPACITY	1 x 400 ml
SHOOTING SPECIFICATION	PROGRAMMABLE IN SECONDS
CYLINDER MODEL	VERTICAL/HORIZONTAL
CYLINDER INCLUDED	1

#### ELECTRICAL SPECIFICATIONS

POWER SUPPLY	230 V or 110 V
AVERAGE POWER CONSUMPTION	37 W
BATTERY PACK	YES
OPTIONAL DEMO/ANTIROBBERY KIT	YES
WIRED INPUTS ARMING AND SHOOTING	YES
WIRED OUTPUTS	YES
STANDARD COMMUNICATION PROTOCOL	YES

#### STANDARDS

COMPLIES WITH EUROPEAN CE	YES
FOG FLUID IS CERTIFIED	YES
MEETS EUROPEAN STANDARD	YES



m<sup>3</sup> 200

### FAST 03 2C

It is the ideal fogging system to protect small and medium areas like shops, homes, bank ATM machines and generally all professional applications where is needed a top security technology. It is equipped with two cylinders for a very convenient, reliable and redundant shooting, shoots up to 200 m<sup>3</sup> of dense fog in 15 seconds. It is very fast and competitive.



Powerful and fast fogging system, can cover up to 200 m<sup>3</sup> in 15 seconds.



The densest fog among all the fogging systems thanks to 80% of glycol in its fog fluid and the proprietary shooting technology.



Removable and disposable fog cylinder, very easy to change and with a very competitive price.



Thanks to the massive insulation UR FOG fogging systems have a very low power consumption and can shoot for a long time in absence of mains power; temperature is constantly stable.



A unique serial bus to plug on the electronic board an add on card that allows to easily interface the machine with alarms and to control the fogging system even from remote. A standard protocol is available for all machines.



UR FOG fogging systems are innovative in their technology and performances, in order to guarantee the most effective protection against thefts and they have different patents.



UR FOG fogging systems are certified after European regulation. Fog fluid is assessed as not dangerous for people and animals and does not leave residuals.

#### GENERAL SPECIFICATIONS

WEIGHT OF THE FOG MACHINE	ABOUT 11 KG
WEIGHT WITH PACKAGING	ABOUT 12 KG
UNITS ON ONE PALLET 100X120	36
DIMENSION OF THE MACHINE	26,5X23,0XH34,5
DIMENSION OF THE PACKAGING	32,0X25,0XH43,0
COLORS	WHITE
WORKING TIME WITHOUT MAINS POWER	ABOUT 2 HOURS
HEAT UP TIME FROM COLD	ABOUT 70 MINUTES
VERTICAL OR CORNER MOUNTING	YES
HORIZONTAL MOUNTING	YES
SERIAL USB PORT FOR MONITORING	YES
NOZZLE TAMPER	YES
SERIAL BUS FOR STANDARD PROTOCOL	YES
ALARM KIT	OPTIONAL

#### FOG GENERATOR

NEW HEATING SYSTEM PLUS	YES
COVERAGE IN A SINGLE SHOT (1,5 M VISIBILITY)	UP TO 300 m <sup>3</sup>
COVERAGE IN A SINGLE SHOT (RECOMMENDED DENSITY)	UP TO 200 m <sup>3</sup>
MAX SECONDS OF FOG EMISSION	15 sec
MAX FOG EMITTED WITH FULL FOG TANK	1200 m <sup>3</sup>
NUMBER OF CYLINDERS	2
FOG TANK CAPACITY	2 x 400 ml
SHOOTING SPECIFICATION	PROGRAMMABLE IN SECONDS
CYLINDER MODEL	VERTICAL / HORIZONTAL
CYLINDER INCLUDED	2
DOUBLE FOG TANK ADVANTAGE	YES

#### ELECTRICAL SPECIFICATIONS

POWER SUPPLY	230 V or 110 V
AVERAGE POWER CONSUMPTION	37 W
BATTERY PACK	YES
OPTIONAL DEMO/ANTIROBBERY KIT	YES
WIRED INPUTS ARMING AND SHOOTING	YES
WIRED OUTPUTS	YES
STANDARD COMMUNICATION PROTOCOL	YES

#### STANDARDS

COMPLIES WITH EUROPEAN CE	YES
FOG FLUID IS CERTIFIED	YES
MEETS EUROPEAN STANDARD	YES



m<sup>3</sup> 400

### FAST 02 2C

It is the ideal fogging system to protect medium areas like large shops, homes, and generally all professional applications where a top security technology is needed. It is equipped with two cylinders for a very convenient, reliable and redundant shooting, shoots up to 400 m<sup>3</sup> of dense fog in 25 seconds. It is very fast and competitive.



Powerful and fast fogging system, can cover up to 400 m<sup>3</sup> in 25 seconds.



The densest fog among all the fogging systems thanks to 80% of glycol in its fog fluid and the proprietary shooting technology.



Patented double fog cylinder is the best solution to shoot fog, tanks are easy to change and disposable. When the first cylinder is empty the machine switches automatically to the second one even during the same shot.



Thanks to the massive insulation UR FOG fogging systems have a very low power consumption and can shoot for a long time in absence of mains power; temperature is constantly stable.



Another exclusive, patented and very useful plus that allows to detect automatically if the nozzle is tampered and sends an advise signal.



A unique serial bus to plug on the electronic board an add on card that allows to easily interface the machine with alarms and to control the fogging system even from remote. A standard protocol is available for all machines.



UR FOG fogging systems are innovative in their technology and performances, in order to guarantee the most effective protection against thefts and they have different patents.



UR FOG fogging systems are certified after European regulation. Fog fluid is assessed as not dangerous for people and animals and does not leave residuals.

#### GENERAL SPECIFICATIONS

WEIGHT OF THE FOG MACHINE	ABOUT 15 KG
WEIGHT WITH PACKAGING	ABOUT 18 KG
UNITS ON ONE PALLET 100X120	27
DIMENSION OF THE MACHINE	30,5X23,0XH39,0
DIMENSION OF THE PACKAGING	37,0X25,0XH47,0
COLORS	WHITE
WORKING TIME WITHOUT MAINS POWER	ABOUT 2 HOURS
HEAT UP TIME FROM COLD	ABOUT 90 MINUTES
VERTICAL OR CORNER MOUNTING	YES
HORIZONTAL MOUNTING	YES
SERIAL USB PORT FOR MONITORING	YES
NOZZLE TAMPER	YES
SERIAL BUS FOR STANDARD PROTOCOL	YES
ALARM KIT	OPTIONAL

#### FOG GENERATOR

NEW HEATING SYSTEM PLUS	YES
COVERAGE IN A SINGLE SHOT (1,5 M VISIBILITY)	UP TO 600 m <sup>3</sup>
COVERAGE IN A SINGLE SHOT (RECOMMENDED DENSITY)	UP TO 400 m <sup>3</sup>
MAX SECONDS OF FOG EMISSION	25 sec
MAX FOG EMITTED WITH FULL FOG TANK	1500 m <sup>3</sup>
NUMBER OF CYLINDERS	2
FOG TANK CAPACITY	2 x 500 ml
SHOOTING SPECIFICATION	PROGRAMMABLE IN SECONDS
CYLINDER MODEL	VERTICAL / HORIZONTAL
CYLINDER INCLUDED	2
DOUBLE FOG TANK ADVANTAGE	YES

#### ELECTRICAL SPECIFICATIONS

POWER SUPPLY	230 V or 110 V
AVERAGE POWER CONSUMPTION	42 W
BATTERY PACK	YES
OPTIONAL DEMO/ANTIROBBERY KIT	YES
WIRED INPUTS ARMING AND SHOOTING	YES
WIRED OUTPUTS	YES
STANDARD COMMUNICATION PROTOCOL	YES

#### STANDARDS

COMPLIES WITH EUROPEAN CE	YES
FOG FLUID IS CERTIFIED	YES
MEETS EUROPEAN STANDARD	YES

m<sup>3</sup> 1200



### FAST 01 2C

It is the most powerful machine in the market, ideal to protect large areas like big shops, warehouses, superstores or even to protect targets in open space. Shoots 1200 m<sup>3</sup> of dense fog in 70 seconds. It is equipped with two removable fog cylinders.



Powerful and fast fogging system, can cover up to 1200 m<sup>3</sup> in 70 seconds.



The densest fog among all the fogging systems thanks to 80% of glycol in its fog fluid and the proprietary shooting technology.



Patented double fog cylinder is the best solution to shoot fog, tanks are easy to change and disposable. When the first cylinder is empty the machine switches automatically to the second one even during the same shot.



Thanks to the massive insulation UR FOG fogging systems have a very low power consumption and can shoot for a long time in absence of mains power; temperature is constantly stable.



Another exclusive, patented and very useful plus that allows to detect automatically if the nozzle is tampered and sends an advise signal.



A unique serial bus to plug on the electronic board an add on card that allows to easily interface the machine with alarms and to control the fogging system even from remote. A standard protocol is available for all machines.



UR FOG fogging systems are innovative in their technology and performances, in order to guarantee the most effective protection against thefts and they have different patents.



UR FOG fogging systems are certified after European regulation. Fog fluid is assessed as not dangerous for people and animals and does not leave residuals.

#### GENERAL SPECIFICATIONS

WEIGHT OF THE FOG MACHINE	ABOUT 22 KG
WEIGHT WITH PACKAGING	ABOUT 25 KG
UNITS ON ONE PALLET 100X120	12
DIMENSION OF THE MACHINE	30,0X35,0XH43,0
DIMENSION OF THE PACKAGING	51,0X39,0XH52,5
COLORS	WHITE
WORKING TIME WITHOUT MAINS POWER	OVER 2,5 HOURS
HEAT UP TIME FROM COLD	ABOUT 2 HOURS
VERTICAL MOUNTING	YES
HORIZONTAL MOUNTING	OPT.
SERIAL/USB PORT FOR MONITORING	YES
NOZZLE TAMPER	YES
SERIAL BUS FOR STANDARD PROTOCOL	YES
ALARM KIT	OPTIONAL

#### FOG GENERATOR

NEW HEATING SYSTEM PLUS	YES
COVERAGE IN A SINGLE SHOT (1,5 M VISIBILITY)	UP TO 1800 m <sup>3</sup>
COVERAGE IN A SINGLE SHOT (RECOMMENDED DENSITY)	UP TO 1200 m <sup>3</sup>
MAX SECONDS OF FOG EMISSION	70 sec
MAX FOG EMITTED WITH FULL FOG TANK	1800 m <sup>3</sup>
NUMBER OF CYLINDERS	2
FOG TANK CAPACITY	2 x 600 ml
SHOOTING SPECIFICATION	PROGRAMMABLE IN SECONDS
CYLINDER MODEL	VERTICAL / HORIZONTAL
CYLINDER INCLUDED	2
DOUBLE FOG TANK ADVANTAGE	YES

#### ELECTRICAL SPECIFICATIONS

POWER SUPPLY	230 V or 110 V
AVERAGE POWER CONSUMPTION	60 W
BATTERY PACK	YES
ANTIROBBERY KIT	YES
WIRED INPUTS ARMING AND SHOOTING	YES
WIRED OUTPUTS	YES
STANDARD COMMUNICATION PROTOCOL	YES

#### STANDARDS

COMPLIES WITH EUROPEAN CE	YES
FOG FLUID IS CERTIFIED	YES
MEETS EUROPEAN STANDARD	YES



## ACCESSORIES

- Cylinder EASY 200 - 2 Shots 300 ml
- Cylinders FAST 03 vertical 400 ml
- Cylinders FAST 03 horizontal 400 ml
- Cylinders FAST 02 vertical 500 ml
- Cylinders FAST 02 horizontal 500 ml
- Cylinders FAST 01 vertical 600 ml
- Cylinders FAST 01 horizontal 600 ml

- Nozzle extension 7cm
- 3 holes nozzle
- Demo Kit
- Antirobbery cable
- Antirobbery button
- Relay board
- Arming key
- Keyfob + receiver
- Transceiver rs232 5/12 V
- WI-FI LAN board with cloud
- LAN board with cloud
- Wall metal bracket




## TEMPEST

AVAILABLE FROM MAY 2020

- FULLY PATENTED
- BATTERY OPERATED
- VERY SMALL
- VERY COMPETITIVE
- FOG NOT SMOKE



## ADD-ON BOARDS




### Relay board

is designed to provide four relay outputs, potentially free.


### LAN BOARD WITH CLOUD




Cloud LAN board to monitor fogging machines and diagnostic. Great advantage for all installers that can check from remote if any maintenance is needed.



Register a new user account



Connect with all installed LAN boards



Check the parameters of all connected machines

### WI-FI LAN BOARD WITH CLOUD



### WI-FI LAN BOARD

The WIFI LAN board allows wired or wireless Lan connection. Through the extremely secure Cloud service, provided for free, it allows, in addition to the systems monitoring, to remotely activate the controls of arming, shooting and setting in seconds the fogging system.

Fully battery operated

Proprietary technology covered by 2 international patents

Patented self balancing shooting system

Battery lasts about one year without mains power

100 m3 (50 cm visibility) in less than 60 seconds

Single shoot fog refill easy to replace

Special custom designed UR FOG battery (non lithium)

Mechanical security system

Real fog and not smoke (not pyrotechnical)

Certified non harmful fog

Compatible with any alarm system

Ideal for wireless alarm integration

OEM version available





**UR FOG S.r.l.**

Sede legale / Legal Office : via Giacinto Collegno n°11 - 10143 Torino - Italy

Sede operativa e magazzini / Operation and delivery to : via Toscana n° 38 - 10099 San Mauro T.se ( Torino ) - Italy

C.F. / P. Iva 10724850010 - Reg. imprese TO - 1157030 - Numero Iscrizione Reg. AEE: IT19050000011412

Numero Iscrizione Reg. Pile Accumulatori IT19100P00005758 Cap. Soc. Euro 10.000 int. versati

Tel. +39 011 0133037 - Fax +39 011 0133005 - e-mail : info@urfog.com

[WWW.URFOG.COM](http://WWW.URFOG.COM)