

DH-NVR5208/5216/5232(-8P)-4KS2

8/16/32CH 1U 4K&H.265 Network Video Recorder



Features

- > Up to 8/16/32 channel IPC input
- > H.265/H.264/MJPEG/MPEG4 codec decoding
- > Max 320Mbps incoming bandwidth
- > Up to 12Mp resolution preview&playback
- > Max 16ch@1080P H.265/H.264 decoding
- > HDMI/VGA simultaneous video output
- > 4/8/16 channel synchronous realtime playback, GRID interface
- > Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek and etc.
- > ONVIF Version 2.4 conformance
- > 3D intelligent positioning with Dahua PTZ camera
- > Support 2 SATA HDDs up to 12TB, 2 USB(1 USB3.0)
- > Support IPC UPnP, 8PoE ports for PoE model
- > Multiple network monitoring: Web, CMS(DSS/Smart PSS) & Mobile phone (DMSS)

DH-NVR5208/5216/5232(-8P)-4KS2


Technical Specifications

Model	DH-NVR5208-4KS2 DH-NVR5208-8P-4KS2		DH-NVR5216-4KS2 DH-NVR5216-8P-4KS2		DH-NVR5232-4KS2 DH-NVR5232-8P-4KS2	
System						
Main Processor	Quad-core embedded processor					
Operating System	Embedded LINUX					
Video& Audio						
IP Camera Input	8 channel		16 channel		32 channel	
Two-way Talk	1 channel Input, 1 channel Output, RCA					
Display						
Interface	1 HDMI (up to 3840x2160), 1 VGA					
Resolution	3840x2160, 1920×1080, 1280×1024, 1280×720, 1024×768					
Display Split	1/4/8/9		1/4/8/9/16		1/4/8/9/16/25/36	
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording					
Recording						
Compression	H.265/H.264/MJPEG/MPEG4					
Resolution	12Mp/8Mp/6Mp/5Mp/4Mp/3Mp/1080P/ 720P/ D1&etc.					
Record Rate	320Mbps					
Bit Rate	16kbps~ 20Mbps for per channel					
Record Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop					
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec					
Video Detection & Alarm						
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Snapshot, Buzzer & Screen tips					
Video Detection	Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank					
Alarm Input	4 channel					
Relay Output	2 channel					
Playback & Backup						
Sync Playback	1/4/9		1/4/9/16		1/4/9/16	
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search					
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom					
Backup Mode	USB Device/Network/Internal SATA burner					
Network						
Ethernet	1 RJ-45 port (10/100/1000Mbps)					
PoE	8 ports (IEEE802.3af/at) for PoE model					
Network Function	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, IP Search(Support Dahua IP camera, DVR, NVS and etc.), P2P					
Max. User Access	128 users					
Smart Phone	iPhone, iPad, Android					
Storage						
Internal HDD	2 SATA ports, up to 12TB					
Auxiliary Interface						

DH-NVR5208/5216/5232(-8P)-4KS2

USB	2 ports (1 Rear USB3.0, 1 Front USB2.0)
RS232	1 port, For PC communication&Keyboard
General	
Power Supply	Single, DC12V/4A for non-PoE model Single, AC 100~240V, 50/60 Hz for PoE model
Power Consumption	NVR: 9.5 W for non-PoE model(without HDD) 15.2W for PoE model(without HDD)
	PoE: Max 25.5W for single port, 130W in total
Working Environment	-10°C~+55°C / 10%~90%RH / 86~106kpa
Dimension (W×D×H)	1U, 375mm×282mm×56mm(non-PoE model) 375mm×327mm×53mm(PoE model)
Weight	1.6KG for non-PoE model(without HDD)
	2.6KG for PoE model(without HDD)

System Connection



*Take NVR5208-8P-4KS2 as an example

Dahua Technology Co., Ltd.

1199'BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email: overseas@dahuatech.com

www.dahuatech.com

*Design and specifications are subject to change without notice.

© 2015 Dahua Technology Co., Ltd.