

## DS-KV8213-WME1 Dual-Button Villa Door Station



### Key Feature

- Standard PoE
- 2 MP HD camera
- Noise suppression and echo cancellation
- Low illumination
- Access control functions
- Tamper-proof
- Configuration remotely via Web
- 2.4 GHz Wi-Fi
- Protection level: IK08



## Specifications

Model	DS-KV8213-WME1	
System parameters	Flash	32 M
	RAM	256M
	Operation method	Two-button
	Operation system	Embedded Linux operation system
Video parameters	Camera	2MP HD camera
	Night vision	Low illumination IR supplement mode: 3 m
	BLC	Support
	DNR	Support
	WDR	True WDR
	Field of view	Horizontal: 129 °, Vertical: 75 °
	Video compression standard	H.264
	Stream	Main stream: 1080p@30fps, 720p@25fps Sub stream: D1@25fps
	Resolution	Main stream: 1920 × 1080p, 720p Sub stream: 704 × 576
	Motion detection	Support
Audio parameters	Anti-flicker frequency	50 Hz, 60 Hz
	Audio intercom	Two-way audio communication
	Audio input	Built-in omnidirectional microphone
	Audio output	Built-in loudspeaker
	Audio compression standard	G.711 U
	Audio compression rate	64 Kbps
Network parameters	Audio quality	Noise suppression and echo cancellation
	Wired network	10/100 M Ethernet
	Network protocol	TCP/IP, RTSP
Access control parameters	Reading frequency	13.56 MHz
	Card type	Mifare card
	Relay	2
	RS-485	1
Interfaces	Wi-Fi	2.4G Wi-Fi
	Debugging port	1
	TF card	Max to 128 G
	Alarm input	4
	Grounding	1
	TAMPER switch	1
	Physical button	2
General	Protection level	IP65, IK08

Indicator	3
Power supply	IEEE802.3af, standard PoE 12 VDC
Power consumption	< 10 W
Heating module	Support
Working temperature	-40 °C to +53 °C (-40 °F to +127.4 °F)
Working humidity	10% to 95%
Installation	Surface mounting/ Flush mounting

The interface functions should be supported by the device.

## Available Model

DS-KV8213-WME1

Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
sateru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com