

DS-7600NI-K2 SERIES NVR



Features and Functions

Professional and Reliable

- Dual-OS design to ensure high reliability of system running
- ANR technology to enhance the storage reliability when the network is disconnected

HD Input

- H.265/ H.265+/H.264/H.264+/MPEG4 video formats
- Connectable to the third-party network cameras
- Up to 32 IP cameras can be connected
- Recording at up to 8 MP resolution
- Supports live view, storage, and playback of the connected camera at up to 8 MP resolution

HD Output

- HDMI and VGA independent outputs provided
- HDMI Video output at up to 4K (3840 × 2160) resolution

HD Storage

- Up to 2 SATA interfaces connectable for recording and backup
- Storage space effectively saved by 50% to 70% with the use of H.264+ decoding format

HD Transmission

- 1 self-adaptive 10 M/100 M/1000 Mbps network interface

Various Applications


- Centralized management of IP cameras, including configuration, information import/export, real-time information display, two-way audio, upgrade, etc.
- Connectable to smart IP cameras from Hikvision and the recording, playing back, and backing up of VCA alarms can be realized
- VCA detection alarm is supported
- Instant playback for assigned channel during multi-channel display mode
- Smart search for the selected area in the video; and smart playback to improve the playback efficiency
- Supports HDD quota and group modes; different capacity can be assigned to different channels
- Hik-Connect for easy network management



Specifications

| Model | | DS-7608NI-K2 | DS-7616NI-K2 | DS-7632NI-K2 |
|----------------------------|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|--------------|--------------|
| Video/ Audio input | IP video input | 8-ch | 16-ch | 32-ch |
| | Incoming bandwidth | 80 Mbps | 160 Mbps | 256 Mbps |
| | Outgoing bandwidth | 160 Mbps | | |
| Video/ Audio output | HDMI output resolution | 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz | | |
| | VGA output resolution | 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz | | |
| | Audio output | 1-ch, RCA (Linear, 1 KΩ) | | |
| Decoding | Decoding format | H.265/H.265+/H.264/H.264+/MPEG4 | | |
| | Recording resolution | 8MP/6MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF | | |
| | Synchronous playback | 8-ch | 16-ch | 16-ch |
| | Capability | 2-ch @ 8 MP (25fps) / 4-ch @ 4MP (30fps) / 8-ch @ 1080p (30fps) | | |
| Network management | Network protocols | TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS | | |
| Hard disk | SATA | 2 SATA interfaces | | |
| | Capacity | Up to 6TB capacity for each HDD | | |
| External interface | Two-way audio | 1-ch, RCA (2.0 Vp-p, 1kΩ) | | |
| | Network interface | 1, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface | | |
| | USB interface | Front panel: 1 × USB 2.0; Rear panel: 1 × USB 3.0 | | |
| | Alarm in/out | 4/1 | | |
| General | Power supply | 12 VDC | | |
| | Power | ≤ 40 W | | |
| | Consumption (without hard disk) | ≤15 W | | |
| | Working temperature | -10 to +55°C (14 to 131°F) | | |
| | Working humidity | 10 to 90 % | | |
| | Chassis | 385 mm chassis | | |
| | Dimensions (W × D × H) | 385 × 315 × 52 mm (15.2" × 12.4" × 2.0") | | |
| Weight (without hard disk) | ≤ 1 kg (2.2 lb) | | | |

Physical Interfaces



| Index | Description | Index | Description |
|-------|-------------------------------------|-------|-----------------------|
| 1 | AUDIO IN | 6 | LAN Network Interface |
| 2 | AUDIO OUT | 7 | USB 3.0 Interface. |
| 3 | VGA Interface | 8 | GND |
| 4 | HDMI Interface | 9 | 12 VDC power supply |
| 5 | Controller Port, Alarm In/Alarm Out | 10 | Power Switch |

Available Models

DS-7608NI-K2, DS-7616NI-K2, DS-7632NI-K2

Distributed by



HIKVISION

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Africa
T +27 (10) 0351172
sale.africa@hikvision.com

Hikvision Europe
T +31-23-55-42-770
info.eu@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Hong Kong
T +852-2151-1761

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Canada
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

Hikvision Korea
T +82-31-731-8841
sales.korea@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision UK
T +01628-902140
support.uk@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com