

Securimport Technology S.L.
Calle 2-B , 11
Parque Empresarial Táctica
46980 Paterna
España



Barrera de exterior de doble haz de 80 a 240 m

DESCRIPTION

Introduction

- ◎ Wired/BUS compatible, 8 sections digital frequency conversion.
 - ◎ Special DSP chip, patented multi-dimensional mistake-corrective code.
 - ◎ Light decorative design, multi installation brackets are optional.
 - ◎ Step-forwarder style fine tuner.
 - ◎ Intelligent power transmission, self-adaptation in environment.
 - ◎ Patented balanced checking,unique digital filtering.
 - ◎ Micro power consumption solid relay.



Model	ABU-20/B	ABU-30/B	ABU-40/B	ABU-60/B	ABU-80/B	ABU-100/B	ABU-150/B
Outdoor detection distance	20m	30m	40m	60m	80m	100m	150m
Indoor detection distance	60m	90m	120m	180m	240m	300m	450m
Number of beams	2						
Light source	Infrared digital pulse	8 sections frequency conversion					
Response speed	50 ~ 700m/s						
Alarm output-normal	Normally close and normally open (NC&NO)	contact capacity AV/DC 30V/0.5mA					
Alarm output-bus	RS-485						
Working voltage	DC 8 ~ 36V; AC 8 ~ 20V						
Working current	40mA	40mA	55mA	55mA	65mA	65mA	70mA
Long-life mode	20mA	20mA	30mA	30mA	35mA	35mA	38mA
Environment	temperature:-25°C ~ 65°C ; humidity:5%~95% (RH)						
Tamper output	Normally close(NC)	contact capacity AV/DC 24V/0.5mA					
Adjust angle	Horizontal:360°; Vertical: $\pm 10^\circ$						
Case material	Germany PC						
Remark	The end with "B" is BUS output system						