## **Product data sheet**



# **AS36RIM-09**

Letrero de color rojo "FUEGO" para sirena de incendio en policarbonato de alta resistencia.

#### General

The AS36RIM-09 is an aesthetic surround for AS360, AS2360, FA360 and FA2300 series VADs, visual indicators, sounders and combination units. It allows for the selected product to be displayed with "FUEGO" text.

The AS36RIM-09 may be retro fitted to compatible deep base devices in the range, and allows for convenient and clear visual verification of the location of fire notification equipment on any installation.

#### Installation

Due to an innovative design, the text orientation of the AS36RIM-09 may either be horizontal or vertical, depending on the application requirements. A locking mechanism prevents the orientation position from being changed once the notification device has been installed.

Designed to accommodate both surface and rear cable entry, the selected, deep base notification device continues to maintain its IP rating as before. The AS36RIM-09 in no way affects the operation or mounting options of the selected notification device, and may be used for compatible addressable and conventional notification devices.

## **Additional text**

Because of the flat surface areas, logos and/or additional text may be added on site as required.



#### Details

- · Easy to install
- Provides and aesthetic surround for fire notification devices
- · Horizontal or vertical installation
- Locking mechanism to lock orientation
- Additional flat surface for logos or text

# AS36RIM-09

Letrero de color rojo "FUEGO" para sirena de incendio en policarbonato de alta resistencia.

# **Technical specifications**

General	
Compatibilidad	300 Series conventional, & 2000 series
	addressable notification devices
Físico	
Dimensiones físicas	43 x 98 x 272 mm (W x H x L)
Peso neto	150 g
Color	Rojo
Tipo de Montaje	Montaje en pared
Posición de montaje	Pared
Material	Policarbonato de alto impacto
Medioambiental	
Antivandálico	No
Entorno	Interior, Exterior
Estándares y regu	ulaciones
Cumplimiento	CE, REACH, RoHS 2



