

# ASW366

**Sirena con flash para montar en pared. Base de perfil bajo. Roja con lente roja.**

## General

The ASW366 is a RED, general purpose, wall mount, electronic sounder and beacon for fire alarm applications. It features a special base containing all wiring connections allowing for easy placement or removal of the device. With an EN54-23 approved coverage pattern of W-2.4-7.5 for the beacon, each ASW366 may be mounted up to 2.4m high and cover a square room of 7.5 x 7.5m with a single device.

## Easy and Fast Installation

The ASx360 series alarm sounder/beacons allow faster installation and maintenance thanks to an innovative mounting base. Dispensing with the need for locking screws these devices use TimeSaver™ bases from the 630 series detector lines. Heads are simply locked onto the base with a “twist and click” action, allowing fitting or removal at any time because the base is the only component that needs to be wired. As the cabling requirement is reduced, commissioning time and costs are naturally reduced as well.

## Efficient and versatile

The ASx360 series sounders provide high sound output at a low current, thus reducing power requirements and system cost. They are supplied with a volume control as standard, allowing final audio adjustments to be made during installation. With a choice of 32 different tones (see tones table in manual), which are switch selectable, the required tone can be selected during installation.

The ASx360 series beacons utilise a specially designed lens giving a uniformed light output over the specified coverage area.

The mechanism for locking the device to the base may be activated if required. Once activated, a special tool is required to remove the sounder from the base.



## Details

- High sound output with Pulse Alert™ technology
- 32 Tones user selectable
- Automatic synchronisation
- Volume control and adjustable flash rate
- Anti-Tamper locking mechanism
- Shallow mouting base with wiring to the base
- Seperate sounder and beacon and control
- EN54:3 and EN54:23 approved, CPR Certified

# ASW366

Sirena con flash para montar en pared. Base de perfil bajo. Roja con lente roja.

## Technical specifications

### General

Monitorización de línea Polarised input

### Eléctrico

Voltaje de funcionamiento 17 to 60 VDC

Consumo de corriente Sounder: 5.1mA  
Beacon: 20mA @ 0.5 Hz

### Sirena

Nivel de salida 85 to 97dB(A) @ 1 m (tone dependant)

Tonos seleccionables 32

Sincronización Phased start

No. de etapas Automatic

### Físico

Dimensiones físicas 100 x 100 mm (Ø x D)  
Shallow base

Peso neto 215 g

Color Rojo

Material Policarbonato de alto impacto

### Medioambiental

Temperatura de funcionamiento -25 to +70°C

Humedad relativa 5 to 95% noncondensing

Entorno Interior

Clasificación IP IP21

### Estándares y regulaciones

Certificación EN54-23, EN54-3

### Operation

Continuous

### EN54-23 rating


Light coverage W-2.4-7.5

Mounting position Wall

Mounting height up to 2.4 m

Floor coverage up to 7.5 x 7.5 m

### EN54-23 Coverage: W-2.4-7.5



As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

Last updated on 15 December 2020 - 17:02

