



YBN-R/4IS(WHT)

Base para detectores intrínsecamente seguros.

General

The YBN-R/4IS(WHT) is a WHITE conventional detector mounting base associated with the conventional range of intrinsically safe detectors which is fully compatible with the majority of existing conventional fire alarm control panels.

Installation

The YBN-R/4IS(WHT) is supplied with square cable clamps for secure and reliable cable termination. Note that this base does not provide line continuity during detector removal (head out support). If manual call points are therefore being used, then these should be wired onto the zone first.



Details

- Low profile
- Rugged design
- Dedicated cable screen terminal
- Accepts from 1 to 2.5 mm² cables
- Quick connection via square cable clamps
- Electronics free

YBN-R/4IS(WHT)

Base para detectores intrínsecamente seguros.

Technical specifications

General

Compatibilidad	Aritech, Kilsen & Ziton conventional zone interfaces
Conectividad	2-wire zone

Físico

Dimensiones físicas	100 x 8 mm
Peso neto	51 g
Color	Blanco
Tipo de Montaje	Montaje en el techo
Entradas de cable	1
Material	ABS
Especificaciones del cable	1 to 2.5 mm ²
No. de núcleos de cable	2
Terminales	6
Marcado funcional	BASEEFA Rating

Medioambiental

Antivandálico	No
Humedad relativa	<95% noncondensing @ 40°C
Entorno	Interior, IS

Estándares y regulaciones

Cumplimiento	CE
Certificación	CENELEC/ATEX

Physical

Fixing centres	48 to 74 mm
----------------	-------------

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

Last updated on 4 March 2020 - 8:28



**United
Technologies**

Climate | Controls | Security