

DMN700L

Pulsador convencional rearmable de alarma, con llave de prueba, montaje de empotrado. Rojo.

General

Installation efficiency, flexibility and full compliance with the latest standards are at the heart of the new MCP indoor call point range.

Installation

Installation time and ultimately cost, are of paramount importance. The MCP range directly reflects this need by providing a unique 'plug and play' concept designed specifically to reduce installation time. All new MCP products utilise a special terminal block, where all initial installation cabling is terminated. This terminal block is then simply connected to the back of the MCP. Simple, but effective, with no re-termination required and no time wasted.

Options and approvals

Through new standards and legislation, both break glass and re-settable operating elements may now be used. To provide the greatest 'flex-ability', the new MCP range can be configured as either a break glass or re-settable unit by simply changing from one element to another. No other additional parts or alternative products are required.

Full compliance with the latest standards is essential and the new MCP indoor call point range is fully approved to the latest EN54-11 standard



Details

- Enhanced aesthetics
- Easy to install (plug and play)
- Surface mount options
- Protection hinged cover with Anti-Tamper facility
- Backward compatible
- Key test facility
- May be used with glass or resettable element
- Easy to replace glass
- High quality micro switch
- Fully approved to the latest standards

DMN700L

Pulsador convencional rearmable de alarma, con llave de prueba, montaje de empotrado. Rojo.

Technical specifications

Eléctrico

Especificaciones del cable	0.5 to 2.5 mm ²
----------------------------	----------------------------

Aislamiento

Resistencia en serie	560 ohm
----------------------	---------

Físico

Peso neto	110 g
-----------	-------

Color	Rojo
-------	------

Material	PC/ABS
----------	--------

Medioambiental

Temperatura de funcionamiento	-10 to +55°C
-------------------------------	--------------

Temperatura de almacenamiento	-10 to +55°C
-------------------------------	--------------

Humedad relativa	0 to 95% noncondensing
------------------	------------------------

Entorno	Interior
---------	----------

Clasificación IP	IP24D
------------------	-------

Estándares y regulaciones

Certificación	EN54-11
---------------	---------

Max. contact rating (resistive load)

2A @ 30 VDC



Como empresa innovadora, Carrier Fire & Security se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 23 December 2021 - 17:10