DS-KIS101-P/Surface Video Intercom Two-Wire Analog Bundle





Key Feature

- 2-Wire plug & play, easy, cost-efficient
- Receive video call and unlock via indoor station
- 7-inch TFT screen with 1024*600 resolution
- 2MP HD colorful camera
- View in color, even in darkness
- One-touch calling with nametag
- IP65 water resistant, preventing from water ingress
- IK7 vandal resistant
- 2 lock relays, power supply for one electric lock (Up to 12V 1A)

Specification

| Door station | | | | |
|----------------------|---|--|--|--|
| Supplement light | IR supplement | | | |
| Lens | Low Illumination 2 MP HD IR Camera | | | |
| FOV | Horizontal: 100 $^\circ$, Vertical: 69 $^\circ$ | | | |
| WDR | Support | | | |
| Resolution | 2MP | | | |
| Door station | | | | |
| Audio input | Built-in omnidirectional microphone | | | |
| Audio output | Built-in loudspeaker (More than 80 dB within 20 cm) | | | |
| Volume adjustment | Adjustable with screwdriver | | | |
| Door station | | | | |
| Alarm input | 4 | | | |
| Two-Wire | 1 | | | |
| TAMPER | 1 | | | |

| Exit button | 2 | | | |
|------------------|---|--|--|--|
| Lock control | 2, lock duration can be adjusted via DIP | | | |
| | switch (Max. 7 s) | | | |
| Door contact | 2 | | | |
| input | 2 | | | |
| Power supply | 1, Max. 12 V 1 A | | | |
| for lock | 1, WIGA, 12 V 1 /7 | | | |
| Debugging port | 1 | | | |
| Door station | | | | |
| Button | 1 | | | |
| Installation | Surface mounting with protective shield | | | |
| Protective level | IP65, IK7 | | | |
| Working | -30 ° C to +60 ° C (-22 ° F to 140 ° F) | | | |
| temperature | -50 C t0 +60 C (-22 F t0 140 F) | | | |
| Working | 10% to 90% | | | |
| humidity | 10% t0 90% | | | |
| Dimensions | 150 mm $	imes$ 82 mm $	imes$ 23.5 mm (5.91" | | | |
| Dimensions | × 3.23" × 0.93") | | | |
| Power supply | 48 VDC, 0.5 A | | | |
| Application | Outdoor | | | |
| environment | Outdoor | | | |
| Power | ≤ 12 W | | | |
| consumption | < 12 VV | | | |
| Door station | | | | |
| Operation | Embedded analog operation system | | | |
| system | Embedded analog operation system | | | |
| Indoor station | | | | |
| Size | 7-inch TFT non-touch screen | | | |
| Operation | 6 touch buttons | | | |
| method | | | | |
| Туре | Colorful TFT screen | | | |
| | | | | |


HIKVISION°


| Resolution | 1024 × 600 | | | |
|------------------------|---|--|--|--|
| Indoor station | | | | |
| Audio input | Built-in omnidirectional microphone | | | |
| Audio output | Built-in loudspeaker (More than 80 dB within 20 cm) | | | |
| Audio quality | / | | | |
| Volume | Adjustable via touch-button | | | |
| Audio | | | | |
| compression | / | | | |
| Rate | | | | |
| Indoor station | | | | |
| Two-wire | 3 | | | |
| Indoor station | | | | |
| Power supply | 48 VDC | | | |
| Power | ≤ 5 W | | | |
| consumption | ≈ 5 ₩ | | | |
| Working temperature | -10 $^\circ$ C to 50 $^\circ$ C (14 $^\circ$ F to 122 $^\circ$ F) | | | |
| Working | 10% to 90% | | | |
| humidity | | | | |
| Dimensions (W | 187 mm \times 137 mm \times 25.4 mm (7.36" | | | |
| \times H \times D) | × 5.39" × 1.00") | | | |
| Installation | Surface mounting | | | |
| Button | 6 | | | |
| Indoor station | | | | |
| Operation system | Embedded analog operation system | | | |
| | | | | |


Available Model

DS-KIS101-P/Surface

Physical Interface









| No. | Description | No. | Description |
|-----|---------------------|-----|-------------------|
| 1 | Screen | 12 | DIP Switch |
| 2 | Microphone | 13 | Debugging Port |
| 3 | Volume + | 14 | Camera |
| 4 | Volume - | 15 | Loudspeaker |
| 5 | Receive /Decline | 16 | Call Button |
| 6 | Unlock Door 2 | 17 | Microphone |
| 7 | Unlock Door 1 | 18 | TAMPER |
| 8 | Monitor /Switch | 19 | Terminals |
| 9 | Terminals | 20 | Debugging Port |
| 10 | Loudspeaker | 21 | DIP Switch |
| 11 | Power Terminal | 22 | Volume Adjust |

Dimension





Unit:mm



23.5

Unit:mm



Distributed by

Γ

HIKVISION°

Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T +1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T +61-2-8599-4233 salesau@hikvision.com

Hikvision India T +91-22-28469900 sales@pramahikvision.com

Hikvision Canada T +1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T +662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T +39-0438-6902

info.it@hikvision.com **Hikvision Brazil** T +55 11 3318-0050

Latam.support@hikvision.com Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T +601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33(0)1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-(0)31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T +62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com

© Hikvision Digital Technology Co., Ltd. 2020 | Data subject to change without notice |