

DS-TMG034



- 79 GHz MMIC with higher resolution and more stable detection.
- Able to recognize the target moving direction, applicable to mixed entrance and exit scenes.
- Adjustable detection distance and width with convenient operation and strong universality.
- Free of learning, applicable to more complex environments.
- Communication via RS-485 or Wi-Fi. Wi-Fi version is equipped with mobile phone application, with which you can debug and upgrade the radar with convenient operation.
- Convenient installation and maintenance with low manual workload and short working hour.
- Adopted with advanced signal processing technology to detect pedestrian and vehicle stably and prevent the boom pole of the barrier gate from falling down when there is pedestrian and vehicle passing.
- Adopted with LED indicators to indicate the radar working status.
- Able to record the configuration parameters of radar automatically. The working status can be restored after the power of the radar is cut off and the radar is rebooted.
- Strong environmental adaptability without influence of the electromagnetic interference, illumination, dust, rain, snow, etc. towards the detection performance.



▪ Specification

Dimensions	
Dimensions (L × W × H)	136.9 × 112.4 × 29 mm (5.4 × 4.4 × 1.1 inch)
Environment	
Working temperature	-40°C ~ +85°C
Power supply	
Working voltage (VDC)	9 to 12 VDC
Working current (A)	< 0.25A
Consumption (W)	< 3W
Technical parameters	
Transmitting frequency (GHz)	79GHz
Transmitting power (mW)	≤ 10mW
Beam width	Vertical 10°, Horizontal 38°
Response time (ms)	50ms
Trigger distance (m)	0.3 to 6 m (adjustable)
Detection area (m)	Horizontal width: 0 to 2 m (adjustable)
Detection target	Vehicle
Area vehicle following	Distinguish following distance of vehicle: 0.5 to 2 m (adjustable)
Online debugging	Serial port/Wi-Fi
Online upgrade	Serial port upgrade
Weight	
Weight	400 g (0.88 lb)

▪ Available Model

DS-TMG034(触发)(海外标配),DS-TMG034(防砸)(海外标配),DS-TMG034(防砸)(大昌行定制)(样机),



Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com