



# EST-PSM48

## Power Supply Manager

### Overview

---

EST-PSM48 Power Supply Manager is designed for distribution of DC Power Supply from Power Supply Units (PSU) and a back-up battery. The unit controls battery charging and distributes power supply to all Voice Evacuation System (VES) equipment at max 60 A. When the system uses battery back-up, the power supplied is 3.2 kW (48 V).

The unit complies with the EN 54-4 VES standards and also EN 12101-10 Smoke and Heat Control System standards.

As a main source of energy distribution, the manager uses external modules 800 W (EST-PS48800) for 48 V.

As a source of stand-by power supply it uses the battery bank of the capacity of up to 200 Ah.

EST-PSM48 cooperates with the 4 x 12 V VRLA battery bank. It maintains the bank in charged condition, ensures temperature compensation of charging parameters and monitors serial resistance of the battery and its wiring as specified in Exhibit No. A2 to the EN 54-4 Standard.

EST-PSM48 co-operates with up to 4 modules of EST-PS4880 Power Supply Units. The manager ensures safe connection for the purpose of parallel operations and monitors the output parameters of each power supply unit.

EST-PS48800 is designed for assembling in a dedicated EST-PF4 Power Supply Unit Frame. The elements of the system are designed for assembling in a Rack 19" IP30-type.



# EST-PSM48

## Power Supply Manager

### Technical specifications

#### Eléctrico

|                      |                     |
|----------------------|---------------------|
| Consumo de corriente | 885 W max. (3.85 A) |
|----------------------|---------------------|

#### Físico

|                     |                               |
|---------------------|-------------------------------|
| Dimensiones físicas | 482 x 85 x 443 mm (W x H x D) |
| Peso neto           | 7.2 kg                        |
| Tipo de montaje     | Bastidor de 19"               |

#### Medioambiental

|                               |               |
|-------------------------------|---------------|
| Temperatura de funcionamiento | -5°C to +40°C |
| Clasificación IP              | 30            |

#### Regulatory

|               |            |
|---------------|------------|
| Certificación | EN54-4     |
| Normativas    | EN12101-10 |

#### Electrical

|                                                                 |                                                                    |
|-----------------------------------------------------------------|--------------------------------------------------------------------|
| AC power supply                                                 | 230 VAC +10% -15%, 50/60 Hz                                        |
| Efficiency at rated power                                       | > 90%                                                              |
| DC input                                                        | 4; bolted terminals; dedicated power supply unit EST-PS48800       |
| DC input protection                                             | 4 x 20 A 58 VDC                                                    |
| DC outputs                                                      | 8 x 48 V, each output max 30 A<br>(total for all 8 outs max. 63 A) |
| Summary maximum DC output load (24 V and 52 V)                  | 3200 W                                                             |
| Charging current                                                | max. 14 A                                                          |
| Charging voltage                                                | 54.6 V $\pm$ 0.6 V (at 25°C)                                       |
| Maximum resistance of wiring and fuses                          | 10 m $\Omega$                                                      |
| Maximum total serial resistance of wiring, fuses, and batteries | 28 - 100 m $\Omega$                                                |

#### Physical

|                       |                                                                                                                   |
|-----------------------|-------------------------------------------------------------------------------------------------------------------|
| Maximum configuration | 1x EST-PSM48 - Power Supply Manager<br>4x EST-PS4880 - Power Supply Unit<br>1x EST-PF4 - Power Supply Units Frame |
| Battery (type)        | 4 pieces, VRLA 12 V 15-200 Ah                                                                                     |



Como empresa innovadora, Carrier Fire & Security se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de [es.firesecurityproducts.com](http://es.firesecurityproducts.com) o póngase en contacto con su comercial.

Last updated on 7 December 2021 - 16:05