

## DS-K1T981MF Iris Recognition Terminal



The terminal adopts deep learning algorithm, which helps to recognize the face and iris with higher accuracy. It can be applied in multiple scenarios, such as buildings, enterprises, financial industries, and other important areas.

- Max. 100,000 faces capacity, Max. 10,000 irises capacity, Max. 100,000 cards capacity, Max. 5000 fingerprint capacity, and Max. 150,000 events capacity
- Iris recognition with 8-inch LCD touch screen; 2 MP wide-angle lens for face recognition and 5 MP single lens for iris recognition; built-in M1 card reading module
- Two-way audio with client software
- Supports TCP/IP, and Wi-Fi
- Configuration via the web client
- Face recognition distance: 0.3 m to 3 m; iris recognition distance: 40 cm to 70 cm
- Face recognition duration < 0.2 s/User and accuracy rate ≥ 99%; iris recognition duration < 1 s
- Supports face with mask recognition



## ▪ Specification


System	
Operation system	Linux
Display	
Dimensions	8-inch
Resolution	800 × 1280
Type	LCD
Operation method	Capacitive touch screen
Video	
Pixel	For face recognition: 2 MP For iris recognition: 5 MP
Lens	× 3 (2 for face recognition, 1for iris recognition)
Video standard	PAL (Default) and NTSC
Network	
Wired network	10 M/100 M/1000 M self-adaptive
Wi-Fi	Support
Interface	
Network interface	1
RS-485	1
Wiegand	1
Lock output	1
Exit button	1
Door contact input	1
IO input	2
IO output	1
TAMPER	1
USB	1
Capacity	
Iris capacity	10,000
Card capacity	100,000
Face capacity	100,000
Fingerprint capacity	5,000
Event capacity	150,000
Authentication	
Iris recognition distance	40 to 70 cm
Iris registration duration	< 5 s
Iris recognition duration	< 1 s
Card type	Mifare 1 card
Card reading frequency	13.56 MHz
Face recognition duration	< 0.2 s
Face recognition accuracy rate	> 99%

Face recognition distance	0.3 to 3 m
Fingerprint recognition duration	< 1 s
<b>Function</b>	
Face anti-spoofing	Support
Time synchronization	Support
<b>General</b>	
Power supply	12 VDC/3 A
Working temperature	-30 °C to 60 °C (-22 °F to 140 °F)
Working humidity	10% to 90% (No condensing)
Dimensions	126 mm × 232 mm × 27 mm (5.0" × 9.1" × 1.1")
Installation	Wall Mounting
Protective level	IP65 (It is recommended using the device indoors for iris recognition)
Language	English

▪ **Available Model**

DS-K1T981MF

▪ **Dimension**



Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com