

# FE260-475

**Retenedor electromagnético de 400N para montaje en suelo/pared con pulsador de desbloqueo.**

## General

---

The FE260-475 is a floor/wall mount door holder with a universal adjustable tube with a reach of 475 mm when used in 180° configuration and 450 mm used in 90° configuration. Which offers a 400N holding force and a release button.

## Magnet construction

---

The magnet is constructed with a pressed coil and anti-remenance pin, giving it a protection of IP54. The protection diodes are integrated into this construction.

## Adjustable

---

The “head” of the FE260-475 allow for two mounting options. The first being the 180° configuration, which is normally used when the door holder is mounted on the wall. In this configuration, the magnet is located “on-top” of the tube.

And the second configuration being the 90° configuration, which is normally used when the door holder is mounted on the ground. In this configuration, the magnet is located on the “side” of the tube, as shown in the picture.

To allow for even more flexibility, the tube can also be cut shorter to match the exact distance required.

## Installer friendly

---

- For practical ease of installation, the door holder comes complete with electrical screw terminals.
- The base is predrilled in a practical, standard format for rapid mounting.
- The door holder is supplied complete with a keeper plate, which offer angular adjustment.

## Approvals

---

The FE260-475 is fully approved according to EN1155.



## Detalles

---

- Low power - 1.6 W
- 400 N holding force
- Anti-remnant ejector
- Spark suppression diode and reverse polarity protection
- Release button
- EN1155 approved
- Adjustable
- Keeper plate included

# FE260-475

Retenedor electromagnético de 400N para montaje en suelo/pared con pulsador de desbloqueo.

## Especificaciones técnicas

---

### General

---

Holding force N (Newton) 400

Release button Yes

Spark suppression diode Yes

Reverse polarity protection Yes

---

### Eléctrico

---

Power supply type 24 VCC

Consumo de corriente 1.6 W

Duty cycle 100%

---

### Físico

---

Physical dimensions 80 x 90 x 450 mm (W x H x D) 90° setup  
80 x 90 x 475 mm (W x H x D) 180° setup

---

### Medioambiental

---

IP rating IP54 (Magnet)

---

### Regulador

---

Standards EN1155

---

### Productos compatibles

---

Categoría	Referencia	Descripción
Retenedores	FE225-150	Soporte para montaje en pared o suelo para la serie FE200. Longitud 150mm.
Retenedores	FE225-300	Soporte para montaje en pared o suelo para la serie FE200. Longitud 300mm.
Retenedores	FE527	Base cuadrada estándar de acero. Dimensiones: 55x18mm.
Retenedores	FE529	Base cuadrada estándar de acero. Eslabón giratorio de 120 grados. Dimensiones: 55x50mm.

---



Como empresa innovadora, Carrier Fire & Security se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de [es.firesecurityproducts.com](http://es.firesecurityproducts.com) o póngase en contacto con su comercial.

Last updated on 19 July 2023 - 9:55